



# FALLTECH<sup>®</sup>

Fall Protection. Precision Engineered.



# BECAUSE LIVES DEPEND ON IT.


We know that the stakes are high. And, when it comes to worker safety, there are no second chances.

That is why...

Fall Protection is all we do...and we take it seriously. Advanced technical design and rigorous quality testing are the backbone of FallTech's manufacturing process. We train and staff fall protection experts that understand problems, not just products, and can identify solutions that save lives.

At FallTech, we engineer innovative height safety solutions as though lives depend on it.

Because they do.



## CONTENTS

Anchorage	26 - 39
Bodywear	40 - 81
Connectors	82 - 109
Devices	110 - 121
Fall Protection Kits	122 - 127
Systems	128 - 131

[www.falltech.com](http://www.falltech.com)

FallTech®  
1306 S. Alameda St.  
Compton, CA  
90221-4803

800.719.4619  
323.752.5613



# DEPEND ON FALLTECH

## ***We Know Fall Protection...***

The best fall protection is to eliminate the fall hazard altogether. We know that isn't always possible. Whether you are trying to prevent a fall with guardrail, trying to restrain a worker from accessing a fall hazard, or you need a personal fall arrest system (PFAS), FallTech can help.

## ***We Know How To Solve Problems...***

Fall protection is about solving problems for workers who are required to work at height. FallTech has a team of engineers, field experts and trainers available to perform hazard analysis and develop product solutions for the most challenging work environments.

## ***We Know The Rules...***

Fall protection at its core is driven by standards and regulations. Both OSHA code and the family of ANSI Z359 standards are central to FallTech's mission to build products that bring you safely home.

## ***We Know Our ABCD's...***

In its simplest form, a personal fall arrest system should be designed to keep you from contacting a lower level if you fall. A personal fall arrest system consists of an anchorage, body wear, connectors and a deceleration device.

### **A – ANCHORAGES**

An anchorage connector is a component that attaches to a structure that is capable of safely supporting impact forces during a fall event. Types of anchorages include multi-purpose, beam, concrete and roofing anchors, sling and grip anchors, wire form hooks, and beam clamps.

### **B – BODY WEAR**

The full body harness is used to enjoin the body with the connecting device in every personal fall arrest system. Full Body Harnesses should be chosen to complement the work to be done with consideration to the work environment. FallTech has a broad range of styles including standard non-belted, belted construction style, vest style, crossover, climbing, tower and retrieval with one to seven D-rings.

### **C – CONNECTORS**

FallTech offers a wide range of connectors - lanyards, lifelines, carabiners and extenders - that couple the full body harness to an anchorage.

### **D – DECELERATION DEVICES**

A deceleration device, such as a self-retracting lifeline, slows the worker and reduces forces to the body and anchorage during a fall.

## ***We Know Your Industry...***

FallTech understands that fall protection requirements are different for each of our customers. That's why we have designed fall protection components and systems for a wide range of work settings and environments.



# BUILDING ON TRUST

## DESIGNED FOR TODAY'S CONSTRUCTION CHALLENGES

FallTech has been on the job for years. We understand the challenges of construction, and have built our fall protection systems around the unique and extensive needs of working in commercial construction. With a full complement of harnesses, lanyards, and anchoring systems, FallTech is standing at the ready to build the future, together...safely.

7089L - PG. 42

7081 - PG. 47

826073 - PG. 84

7035 - PG. 53

7531 - PG. 28



# IT'S A LONG TRIP TO THE TOP...



## ...AND WE ARE IN IT FOR THE DURATION.

Wind energy, telecoms, and electrical towers require specialized workers with the strength and confidence to get the job done. With the critical features to support your work and the comfort to keep you on the job, FallTech's TowerClimber® series of products is there to handle whatever the job demands.

7084 - PG. 51



7042 - PG. 57



8458 - PG. 103



7214 - PG. 35



826073A - PG. 85





# TOUGH JOBS DESERVE TOUGH FALL PROTECTION



## RUGGED FALL PROTECTION FOR EXPLORATION, DRILLING AND REFINING

Derricks, rigs, and platforms can't wait for gear that's not up to the task. FallTech provides a diverse line of quality, time-tested fall protection for petrochemical environments. Whether your system needs call for light duty gear or you are tooling up for a tough job where flame resistance is required, FallTech has personal fall arrest systems you can rely on.

8001BL - PG. 65



8026 - PG. 65



7232 - PG. 112



84202DC - PG. 36



8035L - PG. 67





# WHEN WORKING AT HEIGHTS ISN'T YOUR ONLY PROBLEM



**FALLTECH HAS THE ANSWER**  
When working at heights around high-voltage, don't let your fall protection get in the way of safety. FallTech's Arc Flash series provides a flame-resistant top layer of safety to protect you when you're working at heights and Arc Flash is a serious risk. Third party tested to meet ASTM requirements, Arc Flash harnesses and lanyards combine traditional personal fall arrest systems with the added benefit of flame resistance.



7047 - PG. 71

7051 - PG. 69



72494FT - PG. 35



8242Y3L - PG. 98



8242L - PG. 98





# MAKING A DIFFERENCE IN RESCUE



## SERVING PUBLIC UTILITIES AND MUNICIPALITIES

FallTech has been part of the confined space entry and retrieval plan for over twenty years. With a full complement of rugged yet traditional entry, egress and rescue equipment, FallTech continues to stand at the ready to bring workers home safely.

7027QC - PG. 55

7285 - PG. 118



8208 - PG. 119



7504 - PG. 120



7290 - PG. 118





# BUILT FOR THE ELEMENTS

## WHEN YOU HAVE TO WORK IN PLACES NO ONE WANTS TO GO...

Many jobs come with an expectation of dirt and grime, but too often truly dirty jobs and harsh environments cause unnecessary damage to your fall protection.

FallTech's Titanium® line with MicroShield® technology was developed to help both you and your equipment survive the elements.

...Take the gear that's up to the task.

7078LXT - PG. 75

7008T - PG. 75

84202DC - PG. 36

8256T - PG. 101

826082DT - PG. 101





# A LEADER IN HEIGHT SAFETY FOR EVERY WORKPLACE

## GETTING THE JOB DONE RIGHT

There are no short-cuts to getting the job done right. Whether you are working on or around equipment; in loading areas; tanks, vaults, bins, hoppers; or picking orders, a safe work environment helps you to get the job done.

FallTech's broad portfolio of precision engineered fall arrest equipment is there to keep you safe in even the most precarious situations. FallTech has the right equipment to help you get the job done.



7008 - PG. 59



7232 - PG. 112



8240Y3 - PG. 89



7336 - PG. 35



82563 - PG. 84



7028 - PG. 57



# GEAR FOR THE ROOFTOP

## FALL PROTECTION THAT IS UP TO THE CHALLENGE

We know that your work is difficult and that your time counts. No matter the type of rooftop you work on, FallTech has a solution to keep you safe. Offering single and multi-worker fall protection systems, FallTech delivers the quality, value and ease-of-use needed to comply and get your job done right the first time.

7016 - PG. 61

8150 - PG. 108

7479 - PG. 106

7410 - PG. 33

7431 - PG. 33

7432504 - PG. 38





# KEEPING EMPLOYEES SAFE

## TRAINING AND CONSULTATION

The majority of workplaces at some point have employees exposed to a fall hazard. Providing a combination of passive and active measures is clearly the first step in mitigating the risk of injury or death due to falls from height. However, no matter how effective the equipment, a Fall Protection system will only protect a worker if they know when, where and how it is to be used. Keeping employees safe when fall hazards are present requires planning, forethought and the development of a well-managed fall protection program.

FallTech offers comprehensive consulting, engineering and training services that can help you better understand the hazards where your employees work, help you make those work locations safer, and help train your employees to work safely.

FallTech specializes in helping businesses identify fall hazards, write fall protection plans, and engineer solutions that save lives.

### CONSULTATIVE FALL PROTECTION SERVICES:

- Hazard Analysis
- Site Survey
- Written Job Safety Analysis
- Building Plan Review
- Written Fall Protection Plans
- Jurisdictional Code Review



### ENGINEERED FALL PROTECTION SERVICES:

- Structural Review
- CAD Design
- Customized Equipment Development
- Anchor Point Design



### FALL PROTECTION TRAINING:

- OSHA Compliance
- Competent Fall Protection Equipment Inspector
- ANSI Z359.2-2007 Authorized Person Fall Protection
- ANSI Z359.2-2007 Competent Person Fall Protection



Offering a well-equipped training facility with certified trainers, FallTech provides a full range of in-depth courses in fall protection. A balance of hands on training and classroom instruction provides the optimal training experience. Course offerings range from entry level hazard awareness to the supervisory level competent person training. Additionally, custom courses and site specific trainings are available through our alternative curriculum program.

Regularly scheduled courses are available to attendees at the FallTech Training Center in Compton, CA, and at a variety of regional venues throughout the United States, and at client facilities throughout North America.



ANCHORAGE26A

To ensure maximum safety, FallTech anchorage devices and connectors are thoroughly tested and engineered to adapt to nearly every anchorage need where connection of a fall arrest system is necessary.

ANCHORAGE	26
» Steel	28
» Concrete	30
» Roofing	32
» Multi-purpose	34
» Horizontal Lifeline Kits	37
» Ladder Systems	39



BODY WEAR40B

Designed to meet or exceed applicable OSHA and ANSI standards, FallTech's line of full body harnesses is just as diverse as the people who wear them. We have developed a wide selection of styles and configurations to address the demands of every work place.

FULL BODY HARNESSSES	40
» FlowTech	42
» ComforTech	46
» Journeyman	52
» Tradesman	58
» Contractor	60
SPECIALTY	63
» RoughNeck	64
» Arc Flash	68
» WeldTech	72
» Titanium	74
» High-Vis Vests	76
BELTS AND ACCESSORIES	78
» Work Belts	78
» Accessories	79
» Tool Lanyards	80
» Sizing	81



CONNECTORS82C

FallTech's wide variety of connectors and lanyard configurations are designed to give you flexibility while making safe connections when anchoring off. All of our lanyards are designed to meet or exceed applicable OSHA and ANSI standards.

SHOCK ABSORBING LANYARDS	82
» ViewPack	84
» ElasTech	88
» Internal	92
» FT Basic	94
» Specialty	96
» Titanium	100
POSITIONING/RESTRAINT LANYARDS	102
» Positioning	102
» Restraint	104
VERTICAL ACCESS	106
» Rope Grabs	106
» Rope Grab Lanyard Sets	107
» Vertical Lifelines	108
CARABINERS & EXTENDERS	109
» Extenders	109
» Carabiners	109



DEVICES110D

Purpose-built to exacting requirements, FallTech devices range from precision engineered self-retracting lifelines (SRLs) to a complete line of equipment to facilitate confined space entry, retrieval and rescue.

SELF-RETRACTING LIFELINES	110
» Cable	112
» Web	115
RESCUE	116
» Trauma Relief	116
» Controlled Descent	116
CONFINED SPACE	117
» Tripods	117
» 3-way Retrieval	118
» Winches	118
» Tripod Kits	120





## ANCHORAGE


FallTech's SteelGrip® beam clamps feature lightweight, ergonomic, EasyGrip latch assemblies for quick installation and ease of adjustment. Employing alloy steel jaws and nylon slider pads, SteelGrip Beam Clamps offer a high degree of mobility and smooth trailing behind the worker.

**STEELGRIP® \ Dual Adjust Beam Anchor**

# 7530

# ANCHORAGES

A personal fall arrest system is nothing without a tie off point. Steel, concrete, wood, metal deck...all present challenges when it comes to anchoring your personal fall arrest system. We have developed a wide range of anchorage solutions for even the most challenging work environments.





7531

STEEL \ Trailing Beam Clamp

- Single Ratcheting; Fits 4" to 12" Flange Width; Machined Aluminum Bar; Steel Jaws with Slider Pads.



– 7531 4" to 12"

7530

STEEL \ Trailing Beam Clamp

- Dual Ratcheting for Centering on I-beam; Fits 4" to 14" Flange Width; Machined Aluminum Bar; Steel Jaws with Slider Pads.



– 7530 4" to 14"

7533

STEEL \ Trailing Beam Clamp

- Dual Adjustment for Centering on I-beam; Fits 3" to 13" Flange Width; Aluminum Hex Bar and Jaws.



– 7533 3" to 13"      – 7534 3" to 18"

7535

STEEL \ Stationary Beam Clamp

- Vertical or Horizontal Mount; Aluminum Hex Bar and Jaws; Fits 4" to 12" Flange Width; Can be used for FallTech Temporary HLLs; 8,000 lbs Capacity.



– 7535 4" to 12"      – 7536 10" to 24"

7710

STEEL \ Beam Trolley

- Cast and Machined Aluminum and Steel Construction; Fits 6" to 12" Flange Width; For Temporary or Permanent Installations.




– 7710

7711

STEEL \ Heavy Duty Beam Trolley

- Steel Frame and Wheels; Fits Beam Flanges from 3" to 8" Wide and up to 1.25" Thick; Simple Adjustment with Common 2" Adjustable Wrench; For Temporary or Permanent Installations.



– 7711

7414

STEEL \ Bolt-on

- Forged D-ring and Bolt-on Plate; Provides Simple Overhead Anchorage Solution.



– 7414 2" x 4½ plate with 1/2" holes      – 7414SS 2" x 4½ stainless steel plate with 1/2" holes

7414P

STEEL \ Weld-on

- Forged D-ring and Plain/Uncoated Steel Plate for Weld-on or Bolt-on Applications; Provides Simple Overhead Anchorage Solution.




– 7414P 2" x 4½ plate with 1/2" holes

7407

STEEL \ Wire Form

- Stainless Steel Wire Form Temporary Anchor.



– 7407 4" to 5" Range of Fit  
– 7402 2" to 3" Range of Fit  
– 7403 3" to 4" Range of Fit

7435

STEEL \ Bolt-on

- Forged Alloy Steel Construction; Extra Large Ring Provides Compatibility with a Wide Range of Connectors; Bolt-on Design Provides Simple Overhead Anchorage Solution; Bolt size 9/16" Threaded Stud with Grade 8 Nut; 7/8" Max Substrate Thickness.



– 7435

7408

STEEL \ Grip Anchor

- Alloy Steel Grip Anchor for Temporary/Reusable Anchorage for up to 1¼" Flange Thickness; For Vertical or Horizontal Applications; 10,000 lbs Capacity.



– 7408





CONCRETE

FallTech concrete anchors have been designed for applications where traditional anchors fall short. Whether a temporary solution is needed for pre-cast or pour in place concrete, or if a permanent yet removable anchorage is needed, FallTech concrete anchors provide expected solutions.

Looped end for connection to internal rebar before concrete pour

Tubular polyester jacket provides abrasion and chemical resistance

2-1/2" 5,000 lbs O-ring allows compatibility to a wide variety of deceleration connectors

Rugged 1" inner polyester web provides economical and durable solution for pour-in-place rebar connection

7448

CONCRETE / POUR-IN-PLACE

7448

CONCRETE \ Pour-in-place

– 4' Web Embed Anchor with Jacketed Loop and O-ring.



- 7448 4'
- 7425 2'
- 7436 3'
- 7472 6'
- 7496 8'

7448L

CONCRETE \ Pour-in-place

– 4' Web Embed Anchor with Dual Loops.



- 7448L 4'

7442

CONCRETE \ Temporary Toggle

– Reusable 3/4" Multi-directional Temporary Toggle Anchor for Use in Pre-cast Concrete Structures; Rated to 5,000 lbs.



- 7442 3/4" Max Hole Diameter; 1 1/2" Min to 4" Max Thickness for Precast and 6" Min Thickness for Hollowcore Concrete Applications

CONCRETE \ Anchorage

7440

CONCRETE \ Temporary Wedge

– Reusable 3/4" Multi-directional Temporary Anchor for Use in Existing Cured Concrete Structures; Rated to 5,000 lbs.



- 7440 3/4" Max Hole Diameter and 3" Max Hole Depth

7441

CONCRETE \ Temporary Wedge

– Reusable 1" Multi-directional Temporary Anchor for Use in Existing Cured Concrete Structures; Rated to 10,000 lbs.



- 7441 1" Max Hole Diameter and 4 1/2" Max Hole Depth





# ROOFING

Made from quality materials and engineered for safety, FallTech's wide range of roof anchors are designed to be safe, easy to use and cost-effective.



7432

ROOFING / TEMPORARY REUSABLE

7431

ROOFING \ Permanent

- Double D-ring; Permanent Roof Anchor with Stainless Steel Body; Fastens Under Shingles, Leaving D-rings Exposed for Attachment; 17" Including D-rings with 12" Nailing Surface.



- 7431  
- 7431F with Nails

7434

ROOFING \ Permanent

- Single D-ring, Permanent Roof Anchor with Stainless Steel Body; Fastens Under Shingles, Leaving D-ring Exposed for Attachment; 19" Including D-ring with 17" Nailing Surface.



- 7434

7626

ROOFING \ Permanent

- Vertical Wall Anchor; Stainless Steel with Fasteners; Attaches to Top Plate and Truss or Rafter.



- 7626 Up to 7/12 Roof Pitch



- 7627 8/12 or Greater Roof Pitch

7432

ROOFING \ Temporary Reusable

- Dual Truss-mount Anchor for Horizontal Lifeline Use; Attaches to Sheathing or Trusses; Includes Lag Screws and U-bolts; Mounting Plates are 5" x 12" Each and 24" on Center for Roof Trusses.



- 7432

ROOFING \ Anchorage

7410

ROOFING \ Temporary Reusable

- Reusable, Hinged Roof Anchor with Heavy Duty D-ring; Includes Nails.



- 7410

7410M

ROOFING \ Temporary Reusable

- Reusable, Hinged Roof Anchor with Heavy Duty D-ring for Metal Roofs; Includes Screws.



- 7410M

744410

ROOFING \ Single Use/10pk

- Single-use Roof Anchor; with Nails.



- 744410 10 Pack w/ Nails  
- 7444 Single

7433

ROOFING \ Temporary Reusable

- EcoAnchor; 4' x 4' Water-filled Counter-weight Anchor; with Duffle Bag.



- 7433



MULTI-PURPOSE

Built to meet the site-specific needs of various industries, FallTech multi-purpose anchors are designed for a wide variety of temporary and permanent applications.



Can be passed through multiple times to meet desired overhead height

1-3/4" 8,500 lbs load-bearing web

Fastens to overhead structural member by passing smaller D-ring through larger D-ring

3" wear pad webbing protects primary load-bearing web from cuts and abrasion

3 box stitches for superior strength

7336

MULTI-PURPOSE / PASS THROUGH

7336

MULTI-PURPOSE \ Pass Through

– Web Pass-through Anchor Sling with 2 D-rings and 3" Wear Pad.



- |          |     |          |     |
|----------|-----|----------|-----|
| – 7336   | 3'  | – 7373   | 12' |
| – 7324   | 2'  | – 737214 | 14' |
| – 7348   | 4'  | – 737220 | 20' |
| – 7372   | 6'  | – 737224 | 24' |
| – 737208 | 8'  | – 737230 | 30' |
| – 737210 | 10' | – 737240 | 40' |

7236

MULTI-PURPOSE \ Web Choker

– Heavy-duty Web Choker with 1 D-ring.



- |          |            |
|----------|------------|
| – 7236   | 3' Length  |
| – 7218   | 18" Length |
| – 7224   | 2' Length  |
| – 722448 | 4' Length  |
| – 7272   | 6' Length  |

7236LT

MULTI-PURPOSE \ Web Choker

– Light-duty Web Choker with 1 D-ring.



- |          |            |
|----------|------------|
| – 7236LT | 3' Length  |
| – 7224LT | 2' Length  |
| – 7218LT | 18" Length |

7244

MULTI-PURPOSE \ WeldTech Choker

– WeldTech Kevlar® Choker with 1 D-ring.



- |        |           |
|--------|-----------|
| – 7244 | 6' Length |
| – 7245 | 3' Length |

72493FT

MULTI-PURPOSE \ Arc Flash Choker

– Arc Flash Kevlar® Choker with 1 Coated D-ring.



- |           |           |
|-----------|-----------|
| – 72493FT | 3' Length |
| – 72494FT | 4' Length |

7214

MULTI-PURPOSE \ Tower Choker

– 17" Web Tower Choker with D-ring.



- |        |            |
|--------|------------|
| – 7214 | 17" Length |
|--------|------------|



84202DC

MULTI-PURPOSE \ Carabiner Sling Anchor

– Carabiner Sling Anchor; 2 O-rings and Carabiner; 1/4" Vinyl-coated Galvanized Cable; One Carabiner; Attaches to an O-ring, Leaving 2nd O-ring for Connector Attachment.



84202D

MULTI-PURPOSE \ Carabiner Sling Anchor

– Carabiner Sling Anchor; 2 O-rings and Carabiner; 1/4" Galvanized Cable; One Carabiner; Attaches to an O-ring, Leaving 2nd O-ring for Connector Attachment.



7438

MULTI-PURPOSE \ Cable Pass-through


– Pass-through Sling Anchor; 2 O-rings; 1/4" Galvanized Cable.



7428

MULTI-PURPOSE \ Cable Pass-through

– Pass-through Sling Anchor; 2 O-rings; 1/4" Vinyl Coated Galvanized Cable.



770006

HORIZONTAL LIFELINE KIT \ 2 Person

– 2-person Temporary Horizontal Lifeline Kit Includes Synthetic Rope; Line Tensioner; Two Each: Carabiners, O-rings and Pass-through Anchors; with Storage Bag.



777075

HORIZONTAL LIFELINE KIT \ 4 Person

– 4-person Temporary Horizontal Lifeline Kit Includes Synthetic Rope; Line Tensioner; 4 O-rings; 2 Carabiners; 2 Pass-through Anchors; with Storage Bag.





7432502

HORIZONTAL LIFELINE KIT \ 2 Person

– 2-person Temporary Horizontal Roof Truss System; Includes 2 Dual Truss Roof Anchors; 50' length Synthetic Rope; Line Tensioner; 2 O-rings; 2 Carabiners; with Storage Bag.




– 7432502 50' Length

7432504

HORIZONTAL LIFELINE KIT \ 4 Person

– 4-person Temporary Horizontal Roof Truss System; Includes 2 Dual Truss Roof Anchors; 50' length Synthetic Rope; Line Tensioner; 4 O-rings; 2 Carabiners; with Storage Bag.



– 7432504 50' Length

778000

HORIZONTAL LIFELINE KIT \ 4 Person

– 4-person Temporary Horizontal Roof System; Includes 2 EcoAnchors; Synthetic Rope; Line Tensioner; 4 O-rings; 2 Carabiners; with 2 EcoAnchor Duffle Bags and 1 Storage Bag.



– 778000 75' Length

– 778100 100' Length

776000

LADDER SAFETY SYSTEM

– 6' Vertical Rail Segment with Brackets.



– 776000 6' Vertical Rail Segment with Brackets

– 776002 Joiner Kit for Vertical Rails

– 776003 End-Stop Kit for Vertical Rails

– 876001 Fall Arrestor Grab w/Shock Absorber for Vertical Ladder Rail

SAFE CLIMB

LADDER SAFETY SYSTEM

– Wire Rope Ladder Safety System with Sealed Attenuator and Cable Grab.



– SAFE CLIMB





# BODY WEAR


Built to the highest standards, and with industry leading fit, utility and comfort, FallTech full body harnesses and harness accessories confidently deliver on the promise of safety. With a harness for nearly every workplace, FallTech provides safety at heights without compromise.

## BODY WEAR FEATURES

FlowTech® Full Body Harnesses are extremely lightweight and feature FlowScape® technology, which provides the user with unsurpassed all-day breathability and comfort. Available in standard non-belted, belted construction, climbing and retrieval.

**FLOWTECH® \ Construction Belted**

**# 7089**





7088L

**FLOWTECH \ Belted Construction**  
– 3 D-rings, Back and Side; Tongue Buckle Legs and Quick Connect Chest; FlowScape® Shoulder, Leg and Waist Pads.



- 7088S Small
- 7088M Medium
- 7088L Large
- 7088XL X Large

7089L

**FLOWTECH \ Belted Construction**  
– 3 D-rings, Back and Side; Quick Connect Legs and Chest; FlowScape® Shoulder, Leg and Waist Pads.



- 7089S Small
- 7089M Medium
- 7089L Large
- 7089XL X Large

7086L

**FLOWTECH \ Standard, Non-belted**  
– 1 Back D-ring; Tongue Buckle Legs and Quick Connect Chest, FlowScape® Shoulder, and Leg Pads.



- 7086S Small
- 7086M Medium
- 7086L Large
- 7086XL X Large

7087L

**FLOWTECH \ Standard, Non-belted**  
– 1 Back D-ring; Quick Connect Legs and Chest; FlowScape® Shoulder and Leg Pads.



- 7087S Small
- 7087M Medium
- 7087L Large
- 7087XL X Large

7093L

**FLOWTECH \ Standard, Non-belted**  
– 3 D-rings, Back and Side; Tongue Buckle Legs and Mating Buckle Chest; FlowScape® Shoulder and Leg Pads.



- 7093S Small
- 7093M Medium
- 7093L Large
- 7093XL X Large

7092L

**FLOWTECH \ Standard, Non-belted**  
– 3 D-rings, Back and Side; Quick Connect Legs and Chest; FlowScape® Shoulder and Leg Pads.



- 7092S Small
- 7092M Medium
- 7092L Large
- 7092XL X Large

8097L

**FLOWTECH \ Retrieval, Non-belted**  
– 3 D-rings, Back and Shoulder; Tongue Buckle Legs and Mating Buckle Chest; FlowScape® Shoulder and Leg Pads.



- 8097S Small
- 8097M Medium
- 8097L Large
- 8097XL X Large

7097L

**FLOWTECH \ Retrieval, Non-belted**  
– 3 D-rings, Back and Shoulder; Quick Connect Legs and Chest; FlowScape® Shoulder and Leg Pads.



- 7097S Small
- 7097M Medium
- 7097L Large
- 7097XL X Large



7086LFD

FLOWTECH \ Climbing, Non-belted

- 2 D-rings, Back and Front; Tongue Buckle Legs and Quick Connect Chest; FlowScape® Shoulder and Leg Pads.



- 7086SFD Small
- 7086LFD Large
- 7086XLFD X Large

7091LFD

FLOWTECH \ Climbing, Non-belted

- 4 D-rings, Back, Side and Front; Tongue Buckle Legs and Quick Connect Chest; FlowScape® Shoulder and Leg Pads.



- 7091SFD Small
- 7091MFD Medium
- 7091LFD Large
- 7091XLFD X Large

7087LFD

FLOWTECH \ Climbing, Non-belted

- 2 D-rings, Back and Front; Quick Connect Legs and Chest; FlowScape® Shoulder and Leg Pads.



- 7087SFD Small
- 7087MFD Medium
- 7087LFD Large
- 7087XLFD X Large

7092LFD

FLOWTECH \ Climbing, Non-belted

- 4 D-rings, Back, Side and Front; Quick Connect Legs and Chest; FlowScape® Shoulder and Leg Pads.



- 7092SFD Small
- 7092MFD Medium
- 7092LFD Large
- 7092XLFD X Large

8098

FLOWTECH \ Climbing, Cross-over

- 4 D-rings, Back, Side and Front; Tongue Buckle Legs and Mating Buckle Chest; FlowScape® Shoulder and Leg Pads.



- 8098 UniFit
- 8098X/2X Dual Size XL/2XL

8096

FLOWTECH \ Climbing, Cross-over

- 2 D-rings, Back and Front; Tongue Buckle Legs, and Mating Buckle Chest; FlowScape® Shoulder and Leg Pads.



- 8096 UniFit
- 8096X/2X Dual Size XL/2XL

7098

FLOWTECH \ Climbing, Cross-over

- 4 D-rings, Back, Side and Front; Quick Connect Legs and Chest; FlowScape® Shoulder and Leg Pads.



- 7098 UniFit
- 7098X/2X Dual Size XL/2XL

8095

FLOWTECH \ Climbing, Cross-over

- 2 D-rings, Back and Front; Quick Connect Legs and Chest; FlowScape® Shoulder and Leg Pads.



- 8095 UniFit
- 8095X/2X Dual Size XL/2XL



COMFORTECH®

ComforTech® premium-grade harnesses are built to reduce fatigue through the proprietary incorporation of gel, memory foam and lumbar support - the evolution of comfort. Available in standard non-belted, belted construction, climbing, retrieval, and tower versions.



Shoulder, leg and waist pad assemblies for extreme comfort

Twin torso keepers for stowing idle lanyard connectors

9 adjustment positions on belt and legs for superior fit

Durable ballistic nylon pad exteriors

7081LX

COMFORTECH \ BELTED CONSTRUCTION

7081LX

COMFORTECH \ Belted Construction

– 3 D-rings, Back and Side; Tongue Buckle Legs and Mating buckle Chest; Lumbar-supporting Waist Pad.



- 7081SM Dual-Size SM/M
- 7081LX Dual-Size L/XL
- 70812X 2X Large
- 70813X 3X Large

7080LX

COMFORTECH \ Standard, Non-belted

– 1 Back D-ring; Tongue Buckle Legs and Mating Buckle Chest.



- 7080SM Dual-Size SM/M
- 7080LX Dual-Size L/XL
- 70802X 2X Large
- 70803X 3X Large

7083LX

COMFORTECH \ Belted Construction

– 3 D-rings, Back and Side; Quick Connect Legs and Chest, Lumbar-supporting Waist Pad.




- 7083SM Dual-Size SM/M
- 7083LX Dual-Size L/XL
- 70832X 2X Large
- 70833X 3X Large

7082LX

COMFORTECH \ Standard, Non-belted

– 1 Back D-ring; Quick Connect Legs and Chest.



- 7082SM Dual-Size SM/M
- 7082LX Dual-Size L/XL
- 70822X 2X Large
- 70823X 3X Large



### 7080LX3D

COMFORTECH \ Standard, Non-belted

– 3 D-rings, Back and Side; Tongue Buckle Legs and Mating Buckle Chest.



– 7080SM3D Dual-Size SM/M

– 7080LX3D Dual-Size L/XL

### 7082LX3D

COMFORTECH \ Standard, Non-belted

– 3 D-rings, Back and Side; Quick Connect Legs and Chest.




– 7082SM3D Dual-Size SM/M

– 7082LX3D Dual-Size L/XL

### 7081LXRD

COMFORTECH \ Retrieval, Belted

– 5 D-rings, Back, Side and Shoulder; Tongue Buckle Legs and Mating Buckle Chest; Lumbar-supporting Waist Pad.



– 7081LXRD Dual-Size L/XL


– 7081SMRD Dual-Size SM/M

– 70812XRD 2X Large

### 7083LXRD

COMFORTECH \ Retrieval, Belted

– 5 D-rings, Back, Side and Shoulder; Quick Connect Legs and Chest; Lumbar-supporting Waist Pad.




– 7083SMRD Dual-Size SM/M

– 7083LXRD Dual-Size L/XL

### 7082LXRD

COMFORTECH \ Retrieval, Non-belted

– 3 D-rings, Back and Shoulder; Quick Connect Legs and Chest.



– 7082SMRD Dual-Size SM/M

– 7082LXRD Dual-Size L/XL

### 7081LFD

COMFORTECH \ Climbing, Belted

– 4 D-rings, Back, Side and Front; Tongue Buckle Legs and Mating Buckle Chest; Lumbar-supporting Waist Pad.



– 7081SFD Small

– 7081MFD Medium

– 7081LFD Large


– 7081XLFD X Large

– 70812XFD 2X Large

### 7083LFD

COMFORTECH \ Climbing, Belted

– 4 D-rings, Back, Side and Front; Quick Connect Legs and Chest; Lumbar-supporting Waist Pad.



– 7083SFD Small

– 7083MFD Medium


– 7083LFD Large

– 7083XLFD X Large

### 7080LFD

COMFORTECH \ Climbing, Non-belted

– 2 D-rings, Back and Front; Tongue Buckle Legs and Mating Buckle Chest.



– 7080SFD Small

– 7080MFD Medium

– 7080LFD Large

– 7080XLFD X Large


– 70802XFD 2X Large

– 70803XFD 3X Large

### 7082LFD

COMFORTECH \ Climbing, Non-belted

– 2 D-rings, Back and Front; Quick Connect Legs and Chest.



– 7082SFD Small

– 7082MFD Medium


– 7082LFD Large

– 7082XLFD X Large

### 7082L3DFD

COMFORTECH \ Climbing, Non-belted

– 4 D-rings Back, Side and Front; Quick Connect Legs and Chest.



– 7082S3DFD Small

– 7082M3DFD Medium

– 7082L3DFD Large

– 7082XL3DFD X Large



70672D

COMFORTECH \ Climbing, Cross-over  
– 2 D-rings, Back and Front; Quick Connect Legs and Chest.



- 70672D UniFit
- 70672DX/2X Dual-Size XL/2XL

70674D

COMFORTECH \ Climbing, Cross-over  
– 4 D-rings, Back, Side and Front; Quick Connect Legs and Chest.



- 70674D UniFit
- 70674DX/2X Dual-Size XL/2XL

7084L

COMFORTECH \ Tower Climber®  
– 6 D-rings, Back, Chest, Side and Seat; Tongue Buckle Legs and Quick Connect Chest, Lumbar-supporting Waist Pad and Padded Work Seat.



- 7084S Small
- 7084M Medium
- 7084L Large
- 7084XL X Large

7085L

COMFORTECH \ Tower Climber®  
– 6 D-rings, Back, Chest, Side and Seat; Quick Connect Legs and Chest, Lumbar-supporting Waist Pad and Padded Work Seat.



- 7085S Small
- 7085M Medium
- 7085L Large
- 7085XL X Large





# JOURNEYMAN

High-end construction-grade harnesses equipped for a wide range of fall protection applications. The workhorse of the FallTech line, Journeyman Harnesses stand up to the rigors of all day use. Available in standard non-belted, belted construction, climbing, retrieval, tower and derrick versions.



7035L

JOURNEYMAN \ BELTED CONSTRUCTION

7035L

JOURNEYMAN \ Belted Construction

– 3 D-rings, Back and Side; Tongue Buckle Legs and Mating Buckle Chest, Durable 6" Waist Pad.



- 7035S Small
- 7035M Medium
- 7035L Large
- 7035XL X Large
- 7035XXL 2X Large
- 70353XL 3X Large
- 70354XL 4X Large

7035QCL

JOURNEYMAN \ Belted Construction

– 3 D-rings, Back and Side; Quick Connect Legs and Chest, Durable 6" Waist Pad.



- 7035QCS Small
- 7035QCM Medium
- 7035QCL Large
- 7035QCXL X Large
- 7035QC2X 2X Large
- 7035QC3X4X Dual Size 3XL/4XL

7021

JOURNEYMAN \ Standard, Non-belted

– 1 Back D-ring; Tongue Buckle Legs and Mating Buckle Chest.



- 7021 UniFit
- 7021XL X Large
- 70212XL 2X Large
- 70213X 3X Large
- 70214X 4X Large

7021QC

JOURNEYMAN \ Standard, Non-belted

– 1 Back D-ring; Quick Connect Legs and Chest.



- 7021QC UniFit
- 7021QCXL X Large
- 7021QC2X3X Dual Size 2XL/3XL



7023

JOURNEYMAN \ Standard, Non-belted

– 3 D-rings, Back and Side; Tongue Buckle Legs and Mating Buckle Chest.



- 7023 UniFit
- 7023XL X Large
- 70232X 2X Large
- 70233X 3X Large
- 70234X 4X Large

7023QC

JOURNEYMAN \ Standard, Non-belted

– 3 D-rings, Back and Side; Quick Connect Legs and Chest.



- 7023QC UniFit



7027

JOURNEYMAN \ Retrieval, Non-Belted

– 3 D-rings, Back and Shoulder; Tongue Buckle Legs and Mating Buckle Chest.



- 7027 UniFit
- 70272X 2X Large
- 70273X 3X Large

7027QC

JOURNEYMAN \ Retrieval, Non-belted

– 3 D-rings, Back and Shoulder; Quick Connect Legs and Chest.



- 7027QC UniFit

7034L

JOURNEYMAN \ Retrieval, Belted

– 5 D-rings, Back, Side and Shoulder; Tongue Buckle Legs and Mating Buckle Chest; with Durable 6" Waist Pad.



- 7034S Small
- 7034M Medium
- 7034L Large
- 7034XL X Large
- 7034XX 2X Large
- 70343X 3X Large
- 70344X 4X Large

7034QCL

JOURNEYMAN \ Retrieval, Belted

– 5 D-rings, Back, Side and Shoulder; Quick Connect Legs and Chest; with Durable 6" Waist Pad.



- 7034QCS Small
- 7034QCM Medium
- 7034QCL Large
- 7034QCXL2X Dual Size XL/2XL



7035FDL

JOURNEYMAN \ Climbing, Belted

– 4 D-rings, Back, Side and Front; Tongue Buckle Legs and Mating Buckle Chest with Durable 6" Waist Pad.



- 7035FDS Small
- 7035FDM Medium
- 7035FDL Large
- 7035FDXL X Large

7035QCFDL

JOURNEYMAN \ Climbing, Belted

– 4 D-rings, Back, Side and Front; Quick Connect Legs and Mating Buckle Chest with Durable 6" Waist Pad.



- 7035QCFDS Small
- 7035QCFDM Medium
- 7035QCFDL Large
- 7035QCFDXL X Large

7021FD

JOURNEYMAN \ Climbing, Non-belted

– 2 D-rings, Back and Front; Tongue Buckle Legs and Mating Buckle Chest.



- 7021FD UniFit
- 7021FDXL X Large

7021QCFD

JOURNEYMAN \ Climbing, Non-belted

– 2 D-rings, Back and Front; Quick Connect Legs and Chest.



- 7021QCFD UniFit
- 7021QCFDXL X Large

7029

JOURNEYMAN \ Climbing, Cross-over

– 4 D-rings, Back, Side and Front; Tongue Buckle Legs and Mating Buckle Chest.



- 7029 UniFit
- 7029XL X Large
- 70292X 2X Large
- 70293X 3X Large

7029QC

JOURNEYMAN \ Climbing, Cross-over

– 4 D-rings, Back, Side and Front; Quick Connect Legs and Chest.



- 7029QC UniFit
- 7029QCXL2X Dual Size XL/2XL

7028

JOURNEYMAN \ Climbing, Cross-over

– 2 D-rings, Back and Front; Tongue Buckle Legs and Mating Buckle Chest.



- 7028 UniFit
- 7028X/2X Dual Size XL/2XL

7028QC

JOURNEYMAN \ Climbing, Cross-over

– 2 D-rings, Back and Front; Quick Connect Legs and Chest.



- 7028QC UniFit
- 7028QCX/2X Dual Size XL/2XL

7042L

JOURNEYMAN \ Tower Climber®

– 6 D-rings, Back, Front, Side and Seat; Tongue Buckle Legs and Quick Connect Chest, with Durable 6" Waist Pad and Padded Work Seat Sling.



- 7042S Small
- 7042M Medium
- 7042L Large
- 7042XL X Large



TRADESMAN

Commercial-grade, designed for the professional end-user, Tradesman Harnesses boast premium features that deliver value, long life and durability. Available in standard non-belted and belted construction versions.



5 points of adjustment (chest, legs and torso)

Twin torso keepers for stowing idle lanyard connectors

Forged alloy steel hardware

Paired friction roller adjusters on front torso

7008

TRADESMAN \ Standard, Non-belted

- 1 Back D-ring; Tongue Buckle Legs and Mating Buckle Chest.



- 7008 UniFit
- 7008XL X large
- 7008XX 2X Large
- 70083X 3X Large

7010

TRADESMAN \ Standard, Non-belted

-3 D-rings, Back and Side; Tongue Buckle Legs and Mating Buckle Chest.



- 7010 UniFit
- 7010XL X Large
- 7010XXL 2X Large

7006

TRADESMAN \ Standard, Non-belted

-1 Back D-ring; Mating Buckle Legs and Chest.



- 7006 UniFit
- 7006XL X Large
- 7006XXL 2X Large

7009

TRADESMAN \ Standard, Non-belted

-3 D-rings, Back and Side; Mating Buckle Legs and Chest.



- 7009 UniFit
- 7009XL X Large
- 70092X 2X Large

7078LX

TRADESMAN \ Belted Construction

- 3 D-rings, Back and Side; Tongue Buckle Legs and Mating Buckle Chest; Durable 6" Waist and 10" Shoulder Pads.



- 7078SM Dual Size SM/M
- 7078LX Dual Size L/XL
- 70782X 2X Large

7008

TRADESMAN \ STANDARD NON-BELTED



CONTRACTOR

Contractor Harnesses provide the adjustability, fit and value for the practical workforce. Available in standard non-belted, belted construction, and climbing versions.



5 points of adjustment  
(chest, legs and torso)

Torso keeper for stowing  
idle lanyard connector

Label covers, load impact  
indicators and lanyard keeper

Paired mating buckle  
adjusters on front torso

9 adjustment positions on  
legs for superior fit

7073LX

CONTRACTOR \ BELTED CONSTRUCTION

7073LX

CONTRACTOR \ Belted Construction

– 3 D-rings, Back and Side; Tongue Buckle  
Legs and Mating Buckle Chest; Durable 4"  
Waist and 7" Shoulder Pads.



- 7073LX Dual Size L/XL
- 7073SM Dual Size SM/M
- 70732X 2X Large
- 70733X 3X Large

7017

CONTRACTOR \ Standard, Non-belted

– 3 D-rings, Back and Side; Mating Buckle  
Legs and Chest.



- 7017 UniFit
- 7017XL X Large
- 70172X 2X Large
- 70173X 3X Large

7015

CONTRACTOR \ Standard, Non-belted

– 1 Back D-ring; Mating Buckle Legs  
and Chest.




- 7015 UniFit
- 7015XL X Large
- 70152X 2X Large
- 70153X 3X Large

7016

CONTRACTOR \ Standard, Non-belted

– 1 Back D-ring; Tongue Buckle Legs  
and Mating Buckle Chest.



- 7016 UniFit
- 7016X/2X Dual Size XL/XXL
- 70163X 3X Large



7018

**CONTRACTOR \ Standard, Non-belted**  
– 3 D-rings, Back and Side; Tongue Buckle Legs and Mating Buckle Chest.



- 7018 UniFit
- 7018XL X Large
- 70182X 2X Large
- 70183X 3X Large

7019A

**CONTRACTOR \ Climbing, Cross-over**  
– 2 D-rings, Back and Front; Mating Buckle Legs and Chest; 4 Points of Adjustment.



- 7019A UniFit
- 7019AX/2X Dual Size XL/2XL

7007

**FTBASIC \ Standard, Non-belted**  
– 1 Back D-ring; Mating Buckle Legs and Chest. 3 Points of Adjustment.



- 7007 UniFit
- 7007XL X Large
- 7007XX 2X Large
- 70073X 3X Large

7019B

**CONTRACTOR \ Climbing, Cross-over**  
– 4 D-rings, Back, Side and Front; Mating Buckle Legs and Chest; 4 Points of Adjustment.



- 7019B UniFit
- 7019BX/2X Dual Size XL/2XL

SPECIALTY

Every workplace is unique and worker safety often includes dealing with more than just the fall hazard. With specialty harnesses built for electrical applications, climbing, welding, harsh environments and high visibility, we understand that protecting you doesn't end with the fall hazard. When your workplace demands more than everyday fall protection, FallTech has the solution.



**ROUGHNECK™**  
PETROCHEMICAL INDUSTRY



**ARC FLASH**  
ELECTRIC UTILITIES



**WELDTech™**  
WELDING APPLICATIONS



**TITANIUM®**  
HARSH ENVIRONMENTS



**HIGH-VIS VEST**  
GENERAL INDUSTRY



ROUGHNECK™

RoughNeck™ harnesses are tough-built for petrochemical environments while delivering comfort for all day wear. Available in derrick belted and non-belted bosun derrick, climbing and crossover versions.



8021L

ROUGHNECK \ DERRICK BELTED

Padded dorsal D-ring assembly with rugged outer shell

Twin torso keepers for stowing idle lanyard connectors

Multiple belly board attachment methods on upper or lower torso

Paired friction roller torso adjusters

Multiple D-ring configurations available (sling seat, lumbar/restraint, dorsal extension)

8021L

ROUGHNECK \ Derrick Belted

– 4 D-rings; Restraint, Seat and Extension; Tongue Buckle Legs and Mating Buckle Chest; Waist Pad and Belt; Integral Soft Sling Seat; Upper Torso Mating Buckles for #8031 Belly Belt (sold separately).



- 8021S Small
- 8021M Medium
- 8021L Large
- 8021XL X Large

8026

ROUGHNECK \ Derrick Cross-over Belted

– 5 D-rings, Side, Front, Restraint and Extension; Tongue Buckle Legs and Mating Buckle Chest; Wrap-around Padded Waist Assembly and Belt.



- 8026 UniFit
- 8026X/2X Dual Size XL/2XL

8001BL

ROUGHNECK \ Bosun Derrick

– 7 D-rings, Back, Side, Front, Seat and Extension; Tongue Buckle Legs and Mating Buckle Chest; Waist Pad and Belt; Integral Bosun Board Seat (included).



- 8001BS Small
- 8001BM Medium
- 8001BL Large
- 8001BXL X Large

8001L

ROUGHNECK \ Bosun Derrick

– 7 D-rings, Back, Side, Front, Seat and Extension; Tongue Buckle Legs and Mating Buckle Chest; Waist Pad and Belt; Integral Soft Sling Seat (included).



- 8001S Small
- 8001M Medium
- 8001L Large
- 8001XL X Large



8011L

ROUGHNECK \ Derrick Non-belted

– 3 D-rings, Back and Hip-lifting; Tongue Buckle Legs and Mating buckle Chest; Upper Torso Tongue Buckles for #8033 Belly Belt (sold separately).



- 8011S Small
- 8011M Medium
- 8011L Large
- 8011XL X Large

8006L

ROUGHNECK \ Derrick Non-belted

– 3 D-rings, Back and Hip-lifting; Tongue Buckle Legs and Mating Buckle Chest; Lower Torso Mating Buckles for #8035 Belly Belt (sold separately).



- 8006S Small
- 8006M Medium
- 8006L Large
- 8006XL X Large

8016L

ROUGHNECK \ Derrick Non-belted

– 3 D-rings, Back and Hip-lifting; Tongue Buckle Legs and Mating Buckle Chest; Upper Torso Tongue Buckle Straps for #8037 Belly Belt (sold separately).



- 8016S Small
- 8016M Medium
- 8016L Large
- 8016XL X Large

8007L

ROUGHNECK \ Derrick Non-belted

– 4 D-rings, Back, Hip-lifting and Extension; Tongue Buckle Legs and Mating Buckle Chest; Lower Torso Mating Buckles for #8035 Belly Belt (sold separately).



- 8007S Small
- 8007M Medium
- 8007L Large
- 8007XL X Large

8031L

ROUGHNECK \ Belly Belt

– Mating Buckle Connecting Straps for Upper Torso Attachment; Two Steel Work Positioning Rings; Tongue Buckle Belt (For use with #8021).



- 8031S Small
- 8031M Medium
- 8031L Large
- 8031XL X Large

8033L

ROUGHNECK \ Belly Belt

– Tongue Buckle Connecting Straps for Upper Torso Attachment; Two Steel Work Positioning Rings; Tongue Buckle Belt (For use with #8011).



- 8033S Small
- 8033M Medium
- 8033L Large
- 8033XL X Large

8035L

ROUGHNECK \ Belly Belt

– Mating Buckle Connectors for Lower Torso Attachment; Two Steel Work Positioning Rings; Tongue Buckle Belt (For use with #8006 and #8007).



- 8035S Small
- 8035M Medium
- 8035L Large
- 8035XL X Large

8037L

ROUGHNECK \ Belly Belt

– Tongue Buckle Connectors for Lower Torso Attachment; Two Steel Work Positioning Rings; Tongue Buckle Belt (For use with #8016).



- 8037S Small
- 8037M Medium
- 8037L Large
- 8037XL X Large



– 8039XL

ITEM #	DESCRIPTION	SEAT BOARD	LIFTING D'S	CUSHION	TOOL CLIPS	BELT
8039	Premium Bosun Seat					
	– 8039S Small					
	– 8039M Medium					
	– 8039L Large					
	– 8039XL X Large					
8040	Deluxe Bosun Seat					
8041	Regular Bosun Seat					
8042	Economy Bosun Seat					
8043	8" Lifting Seat					



ARC FLASH

FallTech Arc Flash Harnesses were developed specifically for the electric utilities industry and are independently tested to meet the requirements of ASTM F887, OSHA 1926 and ANSI Z359.1. Available in standard non-belted and belted construction versions.



7047

ARC FLASH \ NON-BELTED

8084R

ARC FLASH \ Nylon \ Belted



7051

ARC FLASH \ Nylon \ Non-belted



8081

ARC FLASH \ Nylon \ Belted



8087R

ARC FLASH \ Nylon \ Non-belted



ITEM #	SIZED*	DORSAL WEB LOOP WITH 2 SIDE D-RINGS	SINGLE WEB LOOP	QUICK CONNECT LEGS, CHEST, BELT w/ LEATHER INSULATORS	MATING BUCKLE LEGS, CHEST, BELT w/ LEATHER INSULATORS	PAIRED FRONT TORSO RESCUE LOOPS	MATING BUCKLE TORSO ADJUSTERS w/ LEATHER INSULATORS	SHOULDER, LEGS, AND WAIST PADS
8081R								
8081								
8084R								
8084								
8087R				(No Belt)				
8087	UniFit			(No Belt)				
7051R					(No Belt)			
7051	UniFit				(No Belt)			

\* For Sized Harnesses, Add: S for Small; M for Medium; L for Large; or XL for X Large to End of Part Number



8070

ARC FLASH \ Nomex® \ Kevlar®



ITEM #	SIZED*	3 COATED D-RINGS BACK AND SIDE	QUICK CONNECT LEGS, CHEST, BELT w/LEATHER INSULATORS	COATED MATING BUCKLE LEGS, CHEST, BELT	PAIRED FRONT TORSO RESCUE LOOPS	COATED MATING BUCKLE TORSO ADJUSTERS	SHOULDER, LEGS, AND WAIST PADS
8070R							
8070							
8073R							
8073							

\* For Sized Harnesses, Add: S for Small; M for Medium; L for Large; or XL for X Large to End of Part Number

8073R

ARC FLASH \ Nomex® \ Kevlar®



8076R

ARC FLASH \ Nomex® \ Kevlar®



ITEM #	SIZED*	NOMEX®/KEVLAR® BLEND WEBBING	1 COATED BACK D-RING	QUICK CONNECT LEGS, CHEST, BELT w/LEATHER INSULATORS	COATED MATING BUCKLE LEGS, CHEST, BELT	PAIRED FRONT TORSO RESCUE LOOPS	COATED MATING BUCKLE TORSO ADJUSTERS
8076R				(No Belt)			
8076	UniFit			(No Belt)			
7047R					(No Belt)		
7047	UniFit				(No Belt)		
7049	UniFit	Nylon			(No Belt)		

\* For Sized Harnesses, Add: S for Small; M for Medium; L for Large; or XL for X Large to End of Part Number

7047

ARC FLASH \ Nomex® \ Kevlar®





WELDTECH™

WeldTech™ harnesses are designed to protect workers where weld spatter or flammable environments present additional risks. Available in standard non-belted versions.



7039

WELDTECH \ STANDARD NON-BELTED

7037

WELDTECH \ Standard, Non-belted

- 1 Back D-ring; Mating Buckle Legs and Chest; Nomex®/Kevlar® Blend Web.



- 7037 UniFit
- 7037XL X Large
- 70372X 2X Large

7039

WELDTECH \ Standard, Non-belted

- 3 D-rings, Back and Side; Quick Connect Legs and Mating Buckle Chest; Nomex®/Kevlar® Blend Web.



- 7039 UniFit
- 7039XL X Large
- 70392X 2X Large

5075A

WELDTECH \ Harness Slag Shield

- Suede Leather Outer Shell, with Polyester Lining Protects Harness Webbing from Burns Caused by Welding Spatter.



- 5075A Dual Size S/M/M
- 5075B Dual Size L/XL

5075C

WELDTECH \ Lanyard Slag Shield

- Suede Leather Outer Shell with Polyester Lining for 6' Single-leg Lanyards, Protects Lanyard Webbing from Burns Caused by Welding Spatter.



- 5075C



TITANIUM®

One of the most durable harnesses available, FallTech Titanium® harnesses combine the benefits of longer life and damage resistance, with the comfort and pliability of traditional personal fall arrest components. Available in standard non-belted and belted construction versions.



Padded dorsal D-ring and shoulder assembly with protective outer skin

Microshield®; a thin film poly-coat technology, provides longer life and superior wear resistance

Twin torso keepers for stowing idle lanyard connectors

Paired friction roller adjusters on front torso

Durable 6" waist pad assembly with protective outer skin

7078LXT

TITANIUM \ BELTED CONSTRUCTION

7078LXT

TITANIUM \ Belted Construction

-3 D-rings, Back and Side; Tongue Buckle Legs and Mating Buckle Chest; Durable 6" Waist Pad.



- 7078SMT Dual Size S/M/M
- 7078LXT Dual Size L/XL

7010T

TITANIUM \ Standard, Non-belted

-3 D-rings, Back and Side; Tongue Buckle Legs and Mating Buckle Chest.



- 7010T UniFit

7008T

TITANIUM \ Standard, Non-belted

-1 Back D-ring; Tongue Buckle Legs and Mating Buckle Chest.



- 7008T UniFit

7008PC

TRADESMAN \ Urethane Coated Web

-1 Back D-ring; Tongue Buckle Legs and Mating Buckle Chest; Friction Torso Adjusters; Urethane Coated Webbing.



- 7008PC UniFit
- 7008XLPC X Large

7006T

TITANIUM \ Standard, Non-belted

-1 Back D-ring; Mating Buckle Legs and Chest.



- 7006T UniFit

7016PC

CONTRACTOR \ Urethane Coated Web

-1 Back D-ring; Tongue Buckle Legs; Mating Buckle Chest and Torso Adjusters; Urethane Coated Webbing.



- 7016PC UniFit
- 7016XLPC X Large
- 70162XPC 2X Large



HIGH-VIS VEST

High-Vis Vest harnesses uniquely combine traditional reflective vests with fully adjustable fall protection bodywear. Available in lime and orange for both ANSI compliant DOT Class 2 reflective, and contractor-grade reflective versions.



**7018LXL**  
HIGH-VIS VEST NON-BELTED \ ANSI CLASS 2

7018LXL

HIGH-VIS VEST \ Non-belted

– 3 D-rings, Back and Side; Tongue Buckle  
Legs and Mating Buckle Chest; Class 2 Vest.



- 7018SML Dual Size SM/M
- 7018LXL Dual Size L/XL
- 70182X3XL Dual Size 2XL/3XL
- 5050 Vest Only

7018LX0

HIGH-VIS VEST \ Non-belted

– 3 D-rings, Back and Side; Tongue Buckle  
Legs and Mating Buckle Chest; Class 2 Vest.



- 7018SM0 Dual Size SM/M
- 7018LX0 Dual Size L/XL
- 70182X3X0 Dual Size 2XL/3XL
- 5055 Vest Only

7015LX0

HIGH-VIS VEST \ Non-belted

– 1 Back D-ring; Mating Buckle Legs and  
Chest, Contractor-grade Reflective Vest.



- 7015SM0 Dual Size SM/M
- 7015LX0 Dual Size L/XL
- 70152X3X0 Dual Size 2XL/3XL
- 5056 Vest Only

7015LXL

HIGH-VIS VEST \ Non-belted

– 1 Back D-ring; Mating Buckle Legs and  
Chest, Contractor-grade Reflective Vest.



- 7015SML Dual Size SM/M
- 7015LXL Dual Size L/XL
- 70152X3XL Dual Size 2XL/3XL
- 5051 Vest Only



7055L

POSITIONING \ Padded

– 2 D-rings, Side; 4" Waist Pad; Removable Belt.



- |         |        |          |          |
|---------|--------|----------|----------|
| – 7055S | Small  | – 7055L  | Large    |
| – 7055M | Medium | – 7055XL | X Large  |
|         |        | – 70552X | 2X Large |

7056L

POSITIONING \ Padded

– 2 D-rings, Side; 4" Waist Pad; Heavy-duty Removable Belt.



- |         |        |          |         |
|---------|--------|----------|---------|
| – 7056S | Small  | – 7056L  | Large   |
| – 7056M | Medium | – 7056XL | X Large |

7095L

WORK BELTS \ Heavy Duty

– 1-3/4" Heavy-duty Webbing Won't Fold When Loaded with Heavy Tools; 7-position Adjustment with Steel Buckle.



- |         |        |          |          |
|---------|--------|----------|----------|
| – 7095L | Large  | – 7095XL | X Large  |
| – 7095S | Small  | – 7095XX | 2X Large |
| – 7095M | Medium | – 70953X | 3X Large |
|         |        | – 70954X | 4X Large |

5070

ACCESSORIES \ Arctic Cooling Band

– Soak in Water; Evaporative Effect Keeps You Cool.



– 5070

7060L

POSITIONING \ Web Support

– 2 D-rings, Side; 3" Integral Web Waist Support.



- |         |        |          |         |
|---------|--------|----------|---------|
| – 7060S | Small  | – 7060L  | Large   |
| – 7060M | Medium | – 7060XL | X Large |

7090L

RESTRAINT \ Padded

– 1 D-ring, Lumbar; 4" Integral Waist Pad.



- |         |        |          |          |
|---------|--------|----------|----------|
| – 7090S | Small  | – 7090XL | X Large  |
| – 7090M | Medium | – 70902X | 2X Large |
| – 7090L | Large  | – 70903X | 3X Large |

5066

ACCESSORIES \ Other

– Replacement Lanyard Keepers; 2 pack.



– 5066



Shirt; 5205 (sized)  
(shown with Arctic Cooling Band)

7004Y

ACCESSORIES \ Shoulder Pads

– Back and Shoulder Pad Assembly for Full Body Harnesses (fits most).



– 7004Y

5001

ACCESSORIES \ Shoulder Pads

– ComforTech Back and Shoulder Assembly for Full Body Harnesses with Gel and Memory Foam (fits most).



– 5001

7004YAF

ACCESSORIES \ Shoulder Pads

– Arc Flash Nomex Shoulder Yoke/Pad Assembly.



– 7004YAF

7004L

ACCESSORIES \ Shoulder Pads

– Slip-resistant Shoulder Pads; Hook and Loop Closures; 1 Pair.



– 7004 7.5" Length – 7004L 10" Length

5003

ACCESSORIES \ Leg Pads

– Comfortech Leg Pad Pair for Full Body Harnesses with Gel and Memory Foam (fits most).



– 5003

5003AF

ACCESSORIES \ Leg Pads

– Arc Flash Nomex Leg Pads; Pair.



– 5003AF



5027B

ACCESSORIES \ Tool Lanyards

– Heavy-duty; 15 lbs Tool Capacity; Loop and Carabiner; Expands from 37" to 43".



- 5027A 10 lbs Tool Capacity; 32" to 43"
- 5027B Single; 37" to 43"
- 5027B10 10 Pack; 37" to 43"

5027C

ACCESSORIES \ Tool Lanyards

– Heavy-duty; 15 lbs Tool Capacity; 2 Carabiners; Expands from 36" to 50".



– 5027C

5027H

ACCESSORIES \ Tool Lanyards

– Heavy-duty; 15 lbs Tool Capacity; Loop and Screw-gate Carabiner; Expands from 38" to 48".



– 5027H

5027E

ACCESSORIES \ Tool Lanyards

– Heavy-duty; 15 lbs Tool Capacity; Speed-clip Loop and Carabiner; Expands from 38" to 50".



– 5027E

5027D

ACCESSORIES \ Tool Lanyards

– 10 lbs Tool Capacity; Speed-clip Loop and Carabiner; Expands from 36" to 43".



– 5027D

5027G

ACCESSORIES \ Tool Lanyards

– Wrist Leash with Speed-clip Loop.



– 5027G

5027F

ACCESSORIES \ Tool Lanyards

– Speed-clip Loops for Interchanging Tools on a Single Leash; (For use with 5027E, 5027D, 5027G).



– 5027F 3 Pack

5027N

ACCESSORIES \ Tool Lanyards

– Heavyweight®; Y-Leg; 25 lbs Tool Capacity; 3 Screw-gate Carabiners; Expands from 35" to 42".



– 5027N

DONNING INSTRUCTIONS



After inspecting the harness, grab the dorsal (back) D-ring and give the harness a shake while lifting harness up. This ensures harness strapping is not tangled.



Unfasten all buckles (mating and/or tongue buckle). Slip one arm through harness making sure dorsal D-ring is on your back. Slip your free arm through other side of harness and position straps on shoulders.



Reach between legs and grab one leg strap. Bring strap up between legs and connect mating or tongue buckle. Repeat for other leg strap.




Connect chest strap by attaching mating buckle closures. Ideal position for your chest strap is about six (6) inches below your shoulders. Adjust waist belt (if included).




Adjust leg and chest straps to size. If you can slip your three lead fingers between yourself and webbing, proper sizing has been achieved.

FULL BODY HARNESS SIZING GUIDE



BELT SIZING GUIDE





## CONNECTORS

ViewPack™ Shock Absorbing Lanyards set the standard for energy absorbing lanyards. A traditional pack-style shock absorber with clear PVC inspection window allows for easy inspection of the internal materials while protective label covers enhance the durability and product lifespan.

**VIEWPACK™ \ Shock Absorbing Lanyard** #8256

# CONNECTORS

FallTech connectors are tested to comply with current ANSI standards and built for a wide range of workplaces. FallTech has worked hard to make sure that when you need to be connected, you have the right equipment for the job.

Rugged 1" polyester webbing provides extreme UV resistance

Exclusive ViewPack design combines integral protection of labels and view-window for inspection of internal energy absorber

Integral label cover to protect warning and inspection labels

Tear-away absorber design limits fall forces to 900 lbs or less



8256

VIEWPACK \ Web

– 6’ Single Leg with 2 Snap Hooks.



- 8256 6’ Length
- 8253 3’ Length
- 8254 4’ Length

82563

VIEWPACK \ Web

– 6- Single Leg with 1 Snap Hook and 1 Rebar Hook.



- 82563 6’ Length
- 82543 4’ Length

82562

VIEWPACK \ Web

– 6’ Single Leg with 2 Snap Hooks and Tie-back D-ring.



- 82562 6’ Length

8257

VIEWPACK \ Web

– 4½’ to 6’ Adjustable, Single Leg with 2 Snap Hooks.



- 8257 4½’ to 6’

82608

VIEWPACK \ Web

– 6’ Y-leg for 100% Tie-off; with 3 Snap Hooks.



- 82608 6’ Length
- 826084 4’ Length

826073

VIEWPACK \ Web

– 6’ Y-leg for 100% Tie-off; with 1 Snap Hook and 2 Rebar Hooks.



- 826073 6’ Length
- 8260734 4’ Length
- 8260733FT 3’ Length

826082D

VIEWPACK \ Web

– 6’ Y-leg for 100% Tie-off; 3 Snap Hooks and 2 Tie-back D-rings.



- 826082D 6’ Length
- 826082D4 4’ Length

8260732D

VIEWPACK \ Web

– 6’ Y-leg for 100% Tie-off; with 1 Snap Hook and 2 Rebar Hooks; and 2 Tie-back D-rings.



- 8260732D 6’ Length

826073ADJ

VIEWPACK \ Web

– 4½’ to 6’ Adjustable Y-leg for 100% Tie-off; with 1 Snap Hook and 2 Rebar Hooks.



- 826073ADJ 4½’ to 6’

8106

VIEWPACK \ Rope

– 6’ Single Leg, 5/8” Premium Polyester Rope, 2 Snap Hooks.



- 8106 6’ Length
- 8103 3’ Length
- 8104 4’ Length

82563A

VIEWPACK \ Aluminum

– 6’ Single Leg; with 1 Aluminum Snap hook and 1 Aluminum Rebar Hook.



- 82563A 6’ Length

826073A

VIEWPACK \ Aluminum

– 6’ Y-leg for 100% Tie-off; with 1 Aluminum Snap Hook and 2 Aluminum Rebar Hooks.



- 826073A 6’ Length

826073A2D

VIEWPACK \ Aluminum

– 6’ Y-leg for 100% Tie-off; with 1 Aluminum Snap Hook and 2 Aluminum Rebar Hooks and 2 Tie-back D-rings.



- 826073A2D 6’ Length

825623A

VIEWPACK \ Aluminum

– 6’ Single Leg; with 1 Aluminum Snap Hook and 1 Aluminum Rebar Hook and Tie-back D-ring.



- 825623A 6’ Length



8357Y3

VIEWPACK \ Vinyl-coated Cable  
– 6' Y-leg for 100% Tie-off; 1/4" Vinyl-coated Cable; with 1 Snap Hook and 2 Rebar Hooks.



– 8357Y3 6' Length

8357Y

VIEWPACK \ Vinyl-coated Cable  
– 6' Y-leg for 100% Tie-off; 1/4" Vinyl-coated Cable; with 3 Snap Hooks.



– 8357Y 6' Length

8357

VIEWPACK \ Vinyl-coated Cable  
– 6' Single Leg, 1/4" Vinyl-coated Cable; with 2 Snap Hooks.



– 8357 6' Length  
– 8356 6' Length Uncoated Cable

83573

VIEWPACK \ Vinyl-coated Cable  
– 6' Single Leg, 1/4" Vinyl-coated Cable; with 1 Snap Hook and 1 Rebar Hook.



– 83573 6' Length

8256ELY3

VIEWPACK \ Elastic Core  
– 4½' to 6' Y-leg for 100% Tie-off; with 1 Snap Hook and 2 Rebar Hooks.



– 8256ELY 4½' to 6'

8256ELY

VIEWPACK \ Elastic Core  
– 4½' to 6' Y-leg for 100% Tie-off; with 3 Snap Hooks.



– 8256ELY 4½' to 6'

8256EL3

VIEWPACK \ Elastic Core  
– 4½' to 6' Single Leg; with 1 Snap Hook and 1 Rebar Hook.



– 8256EL 4½' to 6'

8256EL

VIEWPACK \ Elastic Core  
– 4 ½' to 6' Single Leg; with 2 Snap Hooks.



– 8256EL 4½' to 6'

82608PC

VIEWPACK \ Urethane Coated Web  
– 6' Y-leg for 100% Tie-off; 3 Snap Hooks.



– 82608PC 6' Length

826082DPC

VIEWPACK \ Urethane Coated Web  
– 6' Y-leg for 100% Tie-off; with 3 Snap Hooks and 2 Tie-back D-rings.



– 826082DPC 6' Length

82563PC

VIEWPACK \ Urethane Coated Web  
– 6' Single Leg with 1 Snap Hook and 1 Rebar Hook.



– 82563PC 6' Length

8256PC

VIEWPACK \ Urethane Coated Web  
– 6' Single Leg with 2 Snap Hooks.



– 8256PC 6' Length

826073PC

VIEWPACK \ Urethane Coated Web  
– 6' Y-leg for 100% Tie-off; with 1 Snap Hook and 2 Rebar Hooks.



– 826073PC 6' Length





**ELASTECH®**

ElasTech® Shock-Absorbing Lanyards have all of the advantages of our popular Internal lanyards, plus the added benefit of elasticity to enhance worker mobility and reduce the potential for lanyard entanglement.



Heavy duty tubular polyester outer jacket web resists abrasion and UV

Internal high modulus elastic won't soften from frequent use

Forged steel or aluminum connectors with 3,600 lbs gate strength

Full-length internal energy absorber limits fall forces to 900 lbs or less

**8240Y3**

ELASTECH / INTERNAL ELASTIC

**8240Y3**

ELASTECH \ Internal Elastic

– 4½' to 6'; Adjustable Y-leg for 100% Tie-off; with 1 Snap Hook and 2 Rebar Hooks.



– 8240Y3 4½' to 6'

**8240Y**

ELASTECH \ Internal Elastic

– 4½' to 6'; Adjustable Y-leg for 100% Tie-off; with 3 Snap Hooks.



– 8240Y 4½' to 6'

**8240Y32D**

ELASTECH \ Internal Elastic

– 4½' to 6'; Expanding Y-leg for 100% Tie-off; with 1 Snap Hook and 2 Rebar Hooks; D-ring for SRL Attachment.



– 8240Y32D 4½' to 6'

**8240Y32D2R**

ELASTECH \ Internal Elastic

– 4½' to 6'; Adjustable Y-leg for 100% Tie-off; with 1 Snap Hook and 2 Rebar Hooks; 1 D-ring for SRL Attachment and 2 Rescue D-rings.



– 8240Y32D2R 4½' to 6'

**8240Y2D**

ELASTECH \ Internal Elastic

– 4½' to 6'; Adjustable Y-leg for 100% Tie-off; with 3 Snap Hooks and D-ring for SRL Attachment.



– 8240Y2D 4½' to 6'

**8240Y3L**

ELASTECH \ Internal Elastic

– 4½' to 6'; Adjustable Y-leg for 100% Tie-off; with Loop and 2 Rebar Hooks.



– 8240Y3L 4½' to 6'



82403

ELASTECH \ Internal Elastic

– 4½' to 6'; Adjustable Single Leg; with 1 Snap Hook and 1 Rebar Hook.



– 82403 4½' to 6'

82403L

ELASTECH \ Internal Elastic

– 4½' to 6'; Adjustable Single Leg; with Loop and 1 Rebar Hook.



– 82403L6 4½' to 6'

8240

ELASTECH \ Internal Elastic

– 4½' to 6'; Adjustable Single Leg; with 2 Snap Hooks.



– 8240 4½' to 6'

8240L

ELASTECH \ Internal Elastic

– 4½' to 6'; Adjustable Single Leg; with Loop and 1 Snap Hook.



– 8240L 4½' to 6'



8240Y3A

ELASTECH \ Aluminum

– 4½' to 6'; Adjustable Y-leg for 100% Tie-off; with 1 Aluminum Snap Hook and 2 Aluminum Rebar Hooks.



– 8240Y3A 4½' to 6'

8240YA

ELASTECH \ Aluminum

– 4½' to 6'; Adjustable Y-leg for 100% Tie-off; with 3 Aluminum Snap Hooks.



– 8240YA 4½' to 6'

82403A

ELASTECH \ Aluminum

– 4½' to 6'; Adjustable Single Leg; with 1 Aluminum Snap Hook and 1 Aluminum Rebar Hook.



– 82403A 4½' to 6'

8240Y3A2R

ELASTECH \ Aluminum

– 4½' to 6'; Adjustable Y-leg for 100% Tie-off; with 1 Aluminum Snap Hook and 2 Aluminum Rebar Hooks; 2 Steel Rescue D-rings.



– 8240Y3A2R 4½' to 6'

8240A

ELASTECH \ Aluminum

– 4½' to 6'; Adjustable Single Leg; with 2 Aluminum Snap Hooks.



– 8240A 4½' to 6'





INTERNAL

Internal shock absorbing lanyards are an effective, lightweight alternative to traditional pack lanyards. Internal lanyards are constructed using a tubular web integrated with a continuous-length polyester web shock absorber. In the event of a fall, the compressed lanyard expands and the tubular web acts as a fail-safe to dissipate the forces and arrest the fall.

Full-length internal energy absorber limits fall forces to 900 lbs or less

Durable tubular polyester outer jacket web resists abrasion and UV

3,600 lbs gate strength on all steel connectors

Contrasting load-indicator stitch displays when a fall event has occurred

8259Y3

INTERNAL / TUBULAR WEB

8259Y3

INTERNAL \ Tubular Web

– 6' Y-leg for 100% Tie-off; with 1 Snap Hook and 2 Rebar Hooks.



– 8259Y3 6' Length

8259Y3L

INTERNAL \ Tubular Web

– 6' Y-leg for 100% Tie-off; with 1 Loop and 2 Rebar Hooks.



– 8259Y3L 6' Length

8259Y

INTERNAL \ Tubular Web

– 6' Y-leg for 100% Tie-off; with 3 Snap Hooks.



– 8259Y 6' Length

8259YL

INTERNAL \ Tubular Web

– 6' Y-leg for 100% Tie-off; with 1 Loop and 2 Snap Hooks.



– 8259YL 6' Length

8259

INTERNAL \ Tubular Web

– 6' Single Leg; with 2 Snap Hooks.



– 8259 6' Length

8259L

INTERNAL \ Tubular Web

– 6' Single Leg; with 1 Loop and 1 Snap Hook.



– 8259L 6' Length

82593

INTERNAL \ Tubular Web

– 6' Single Leg; with 1 Snap Hook and 1 Rebar Hook.



– 82593 6' Length

82593L

INTERNAL \ Tubular Web

– 6' Single Leg; with 1 Loop and 1 Rebar Hook.



– 82593L 6' Length



**FT BASIC®**

FT Basic® lanyards are compliance-grade without compromising performance or safety.

Rugged 1" polyester webbing provides extreme UV resistance

3,600 lbs gate strength on all steel connectors

Tear-away absorber design limits fall forces to 900 lbs or less

Soft Pack cover protects tear-away energy absorbing web which limits fall forces to 900 lbs or less

Polyester label cover protects warning and inspection labels

**8256LT**

FT BASIC / SOFT PACK

**8256LT**

FT BASIC \ Soft Pack

– 6' Single Leg; with 2 Snap Hooks.



– 8256LT 6' Length

**8256LTL**

FT BASIC \ Soft Pack

– 6' Single Leg; with 1 Loop and 1 Snap Hook.



– 8256LTL 6' Length

**8256LT3**

FT BASIC \ Soft Pack

– 6' Single Leg; with 1 Snap Hook and 1 Rebar Hook.



– 8256LT3 6' Length

**8256LTY**

FT BASIC \ Soft Pack

– 6' Y-leg for 100% Tie-off; with 3 Snap Hooks.



– 8256LTY 6' Length

**8256LTY3**

FT BASIC \ Soft Pack

– 6' Y-leg for 100% Tie-off; 1 Snap Hook and 2 Rebar Hooks.



– 8256LTY3 6' Length

**8256LTD**

FT BASIC \ Soft Pack

– 6' Single Leg; with 2 Snap Hooks and Single Tie-back D-ring.



– 8256LTD 6' Length  
– 8256LTY2D Y-leg; 3 Snap Hooks



SPECIALTY

FallTech has a wide variety of lanyards designed for specialty applications. Whether you are looking for a tie-back lanyard, extended free-fall or something that is able to survive extreme environments, we have all the bases covered.



8241Y

WRAPTECH® / VIEWPACK

8241Y

WRAPTECH® \ ViewPack

– 6' Y-leg for 100% Tie-off; with 1 Snap Hook and 2 x 5,000 lbs Gate Carabiners for Tie-back.



– 8241Y 6' Length

8247Y

IRONMAN® \ Internal

– 6' Y-leg for 100% Tie-off; 12' Extended Freefall; with 1 Swivel Snap Hook and 2 Snap Hooks.



– 8247Y 6' Length

8247Y3

IRONMAN® \ Internal

– 6' Y-leg for 100% Tie-off; 12' Extended Freefall; 1 Snap Hook and 2 Rebar Hooks.



– 8247Y3 6' Length

8248Y

IRONMAN® \ Internal

– 6' Y-leg for 100% Tie-off; 12' Extended Freefall; with 1 Swivel Snap Hook and 2 x 5,000 lbs Gate Carabiners.



– 8248Y 6' Length

8241

WRAPTECH® \ ViewPack

– 6' Single Leg; with 1 Snap Hook and 1x 5,000 lbs Gate Carabiner for Tie-back.



– 8241 6' Length

8247

IRONMAN® \ Internal

– 6' Single Leg; 12' Extended Freefall; with 2 Snap Hooks.



– 8247 6' Length

82473

IRONMAN® \ Internal

– 6' Single Leg; 12' Extended Freefall; with 1 Snap Hook and 1 Rebar Hook.



– 82473 6' Length

8248

IRONMAN® \ Internal

– 6' Single Leg; 12' Extended Freefall; with 1 Snap Hook and 1 x 5,000 lbs Gate Carabiner.



– 8248 6' Length



82463

HEAVYWEIGHT® \ Internal

– 6’ Single Leg; 400 lbs Capacity;  
1 Snap Hook and 1 Rebar Hook.



– 82463 6’ Length

8246Y3

HEAVYWEIGHT® \ Internal

– 6’ Y-leg for 100% Tie-off; 400 lbs Capacity;  
with 1 Swivel Snap Hook and 2 Rebar Hooks.



– 8246Y3 6’ Length

8242L

ARC FLASH \ Soft Pack

– 6’ Single Leg; with 1 Loop and 1 Snap Hook;  
Kevlar® and Nomex® Web; Meets ASTM F887  
Requirements.



– 8242L 6’ Length

82423L

ARC FLASH \ Soft Pack

– 6’ Single Leg; with 1 Loop and 1 Rebar Hook;  
Kevlar® and Nomex® Web; Meets ASTM F887  
Requirements.



– 82423L 6’ Length

8246

HEAVYWEIGHT® \ Internal

– 6’ Single Leg; 400 lbs Capacity;  
with 2 Snap Hooks.



– 8246 6’ Length

8246Y

HEAVYWEIGHT® \ Internal

– 6’ Y-leg for 100% Tie-off; 400 lbs Capacity;  
with 1 Swivel Snap Hook and 2 Snap Hooks.



– 8246Y 6’ Length

8242YL

ARC FLASH \ Soft Pack

– 6’ Y-leg for 100% Tie-off; with 1 Loop and  
2 Snap Hooks; Kevlar® and Nomex® Web;  
Meets ASTM F887 Requirements.



– 8242YL 6’ Length

8242Y3L

ARC FLASH \ Soft Pack

– 6’ Y-leg for 100% Tie-off; with 1 Loop and  
2 Rebar Hooks; Kevlar® and Nomex® Web;  
Meets ASTM F887 Requirements.



– 8242Y3L 6’ Length

8242

WELDTECH \ Soft Pack

– 6’ Single Leg; with 2 Snap Hooks;  
Kevlar® and Nomex® Web.



– 8242 6’ Length

8242Y

WELDTECH \ Soft Pack

– 6’ Y-leg for 100% Tie-off; with 3 Snap Hooks;  
Kevlar® and Nomex® Web.



– 8242Y 6’ Length

8243

WELDTECH \ Internal

– 6’ Single Leg; with 2 Snap Hooks;  
Nomex® Jacket.



– 8243 6’ Length

8243Y

WELDTECH \ Internal

– 6’ Y-leg for 100% Tie-off; with 3 Snap Hooks;  
Nomex® Jacket.



– 8243Y 6’ Length

82423

WELDTECH \ Soft Pack

– 6’ Single Leg; with 1 Snap Hook and 1 Rebar  
Hook; Kevlar® and Nomex® Web.



– 82423 6’ Length

8242Y3

WELDTECH \ Soft Pack

– 6’ Y-leg for 100% Tie-off; with 1 Snap Hook and  
2 Rebar Hooks; Kevlar® and Nomex® Web.



– 8242Y3 6’ Length

82433

WELDTECH \ Internal

– 6’ Single Leg; with 1 Snap Hook  
and 1 Rebar Hook; Nomex® Jacket.



– 82433 6’ Length

8243Y3

WELDTECH \ Internal

– 6’ Y-leg for 100% Tie-off; with 1 Snap Hook  
and 2 Rebar Hooks; Nomex® Jacket.



– 8243Y3 6’ Length



TITANIUM®

Designed to be the most durable lanyards on the market today, FallTech Titanium® Series combines all the benefits of polyurethane coated lanyards with the comfort and pliability of traditional personal fall arrest systems.



826073T

TITANIUM / SHOCK ABSORBING LANYARDS

826073T

TITANIUM \ View Pack

– 6' Y-leg for 100% Tie-off; Coated Web; with 1 Snap Hook and 2 Rebar Hook and 2 Rebar Hooks.



– 826073T 6' Length

8256T

TITANIUM \ View Pack

– 6' Single Leg; Coated Web; with 2 Snap Hooks.



– 8256T 6' Length

826082DT

TITANIUM \ View Pack

– 6' Y-leg for 100% Tie-off; Coated Web; 3 Snap Hooks; 2 Tie-back D-rings.



– 826082DT 6' Length

82608T

TITANIUM \ View Pack

– 6' Y-leg for 100% Tie-off; Coated Web; with 3 Snap Hooks.



– 82608T 6' Length

82563T

TITANIUM \ View Pack

– 6' Single Leg; Coated Web; with 1 Snap Hook and 1 Rebar Hook.



– 82563T 6' Length





POSITIONING

Positioning lanyards or rebar assemblies are designed for use on vertical work surfaces.



Rebar hook features swivel with ANSI compliant 3,600 lbs gate

Swivel rebar hook provides tangle-resistant connection to vertical member

High-strength welded link grade 80 chain provides unsurpassed durability

Clevis-pin snap hooks reduce the need for additional connecting parts

8250

CHAIN / REBAR POSITIONING ASSEMBLY

8250

CHAIN \ Rebar Positioning Assembly

– Swivel Steel Rebar Hook with 2.5” Gate Opening; Clevis-pin Steel Snap Hooks; Grade 80 Chain.



- 8250 23”
- 825010LK 19”
- 82506L 17”

8250LT

CHAIN \ Rebar Positioning Assembly

– Steel Rebar Hook with 2.5” Gate Opening; Clevis-pin Steel Snap Hooks; Grade 80 Chain.



- 8250LT 21”
- 8250LT10LK 17”

8250A

CHAIN \ Rebar Positioning Assembly

– Aluminum Rebar Hook with Swivel and 2.5” Gate Opening; Clevis-pin Steel Snap Hooks; Grade 80 Chain.



- 8250A 24”

8250LTWA

WEB \ Rebar Positioning Assembly

– Aluminum Rebar Hook with 2.5” Gate Opening; Aluminum Snap Hooks; Two-layer Jacketed Web for Wear Resistance.



- 8250LTWA 24”

POSITIONING \ Rebar and Tower

103

CONNECTORS

8250W

WEB \ Rebar Positioning Assembly

– Swivel Steel Rebar Hook with 2.5” Gate; 2 Steel Snap Hooks; 2 Layer Jacketed Web.



- 8250W 23”
- 825012W 19”
- 8250LTW 24”
- Non-swivel

8457

TOWER \ Positioning Assembly

– Spreader Hook with Carabiner.



- 8457 4” Length
- 8456 Hook Only

8458

TOWER \ Positioning Assembly

– Spreader Hook with Carabiner and Swivel Rebar Hook.



- 8458 16” Length

8459

TOWER \ Positioning Assembly

– Spreader Hook with Swivel Rebar Hook and Web Extension.




- 8459 18” Length



RESTRAINT

Restraint Lanyards are intended to be used on platforms, in buckets and other areas to prevent the possibility of a fall. Different lengths and types are available to restrict leading edge access. Restraint lanyards can be attached to the back D-ring on a full body harness or restraint belt.



8206

WEB / RESTRAINT LANYARD

8206

WEB \ Restraint Lanyard

– 6' Single Leg; with 2 Snap Hooks.



- |          |           |           |           |
|----------|-----------|-----------|-----------|
| – 8206   | 6' Length | – 8204    | 4' Length |
| – 820324 | 2' Length | – 82065FT | 5' Length |
| – 8203   | 3' Length | – 82068   | 8' Length |

8209

WEB \ Restraint Lanyard

– 4' to 6' Adjustable Single Leg; 2 Snap Hooks.



- |         |          |          |            |
|---------|----------|----------|------------|
| – 8209  | 4' to 6' | – 820910 | 6' to 10'  |
| – 82098 | 5' to 8' | – 820912 | 7' to 12'  |
|         |          | – 820920 | 11' to 20' |

82063

WEB \ Restraint Lanyard

– 6' Single Leg; with 1 Snap Hook and 1 Rebar Hook.



- |         |           |         |           |
|---------|-----------|---------|-----------|
| – 82063 | 6' Length | – 82033 | 3' Length |
|         |           | – 82043 | 4' Length |

82093

WEB \ Restraint Lanyard

– 4' to 6' Adjustable Leg; with 1 Snap Hook and 1 Rebar Hook.



- |         |          |
|---------|----------|
| – 82093 | 4' to 6' |
|---------|----------|

8206YS

WEB \ Restraint Lanyard

– 6' Y-leg for 100% Tie-off; with 2 Snap Hooks, with 1 Swivel Snap Hook.



- |          |           |
|----------|-----------|
| – 8206YS | 6' Length |
|----------|-----------|

8206Y

WEB \ Restraint Lanyard

– 6' Y-leg for 100% Tie-off; with 3 Snap Hooks.




- |         |           |
|---------|-----------|
| – 8206Y | 6' Length |
|---------|-----------|



8306

CABLE \ Restraint Lanyard

– 6’ Single Leg; 1/4” Galvanized Wire Cable; with 2 Snap Hooks.



– 8306	6’
– 830636	3’
– 83064	4’
– 83065	5’

8156

ROPE \ Restraint Lanyard

– 6’ Single Leg; 5/8” Premium Polyester Rope; with 2 Snap Hooks.



– 8156	6’
– 8153	3’
– 8154	4’

7479

ROPE GRAB \ Vertical Access

– Self-tracking; Hinged; for 5/8” Rope; Coated Steel; with Secondary Safety Latch.



– 7479

7491

ROPE GRAB \ Vertical Access

– Self-tracking; Hinged; for 5/8” Rope; Stainless Steel; with Secondary Safety Latch.




– 7491

8307

CABLE \ Restraint Lanyard

– 6’ Single Leg; 1/4” Vinyl Coated Galvanized Wire Cable; with 2 Snap Hooks.




– 8307	6’
– 830708	8’
– 830710	10’
– 830736	3’

81563

ROPE \ Restraint Lanyard

– 6’ Single Leg; 5/8” Premium Polyester Rope; with 1 Snap Hook and 1 Rebar Hook.



– 81563	6’
– 81533	3’
– 81543	4’

7609

CABLE GRAB \ Vertical Access

– Self-tracking; Hinged; for 3/8” Cable.



– 7609

7355NL

ROPE GRAB \ Vertical Access

– Self-tracking; Hinged; for 5/8” Rope; with Park Function.



– 7355NL

8358

ROPE GRAB LANYARD SET \ Vertical Access

– 3’ Single Leg; ViewPack; with Hinged Self-Tracking Rope Grab; 1 Snap Hook; For 5/8” Rope.



– 8358 3” Length

8368

ROPE GRAB LANYARD SET \ Vertical Access

– 3’ Single Leg; ViewPack; with Self-Tracking Rope Grab; 1 Snap Hook; For 5/8” Rope.



– 8368 3” Length

8355

ROPE GRAB LANYARD SET \ Vertical Access

– 3’ Single Leg; ViewPack; with Deluxe Self-Tracking/Park Rope Grab.



– 8355 3” Length

8353

ROPE GRAB LANYARD SET \ Vertical Access

– 3’ Single Leg; ViewPack; with Manual/Park Rope Grab; 1 Snap Hook; For 5/8” Rope.



– 8353 3” Length

8353LT

ROPE GRAB LANYARD SET \ Vertical Access

– 3’ Single Leg; Soft Pack; with 1 Snap Hook and Manual/Park Rope Grab; For 5/8” Rope.



– 8353LT 3” Length





8150

ROPE \ Lifelines

– 50' x 5/8" Premium Polyester Rope; with 1 Snap Hook and Braid-end.



- 8150 50' Length
- 8125 25' Length
- 8175 75' Length
- 8200 100' Length
- 8150S 150' Length
- 8200S 200' Length

8149

ROPE \ Lifelines

– 50' x 5/8" Copolymer Rope; with 1 Snap Hook and Braid- or Taped-end.



- 8149 Braid-end
- 8149T Taped-end

8150T

ROPE \ Lifelines

– 50' x 5/8" Premium Polyester Rope; with 1 Snap Hook and Taped-End.



- 8150T 50' Length
- 8120T 20' Length
- 8125T 25' Length
- 8130T 30' Length
- 8175T 75' Length
- 8200T 100' Length

8150DH

ROPE \ Lifelines

– 50' x 5/8" Premium Polyester Rope; with 2 Snap Hooks.



- 8150DH 50' Length
- 8125DH 25' Length
- 8175DH 75' Length
- 8200DH 100' Length

8151

ROPE \ Lifelines

– 50' x 5/8" Premium Polyester Rope; Thimble and Braid-End.



- 8151 50' Length
- 8126 25' Length
- 8201 100' Length
- 8151T 50' Length

7120

COUNTER WEIGHT

– Counter Weight; 5 lbs for Vertical Lifelines; Chokes to Trailing End to Keep Line Taught.




– 7120

8447

STEEL \ Carabiner

– Large Twist Lock; 2 1/4" Opening; 3,600 lbs Gate; with Captive Pin Option.




– 8447

8445

STEEL \ Carabiner

– Compact Twist Lock; 7/8" Opening; 3,600 lbs Gate.




– 8445

8450

STEEL \ Carabiner

– Medium Twist Lock; 1" Opening; 3,600 lbs Gate; with Captive Pin Option.



– 8450

83662D

D-RING EXTENDERS \ Extenders

– 18" Web with Snap Hook and 2nd D-ring for SRL Attachment.




– 83662D 18"

8447A

ALUMINUM \ Carabiner

– Large Twist Lock; 2" Gate Opening; 3,600 lbs Gate; with Captive Pin Option.



– 8447A

8466A

ALUMINUM \ Carabiner

– Medium Twist Lock; 7/8" Gate Opening; 3,600 lbs Gate; with Captive Pin Option.



– 8466A

8366

D-RING EXTENDERS \ Extenders

– 18" Web with Snap Hook and D-ring.



- 8366 18"
- 8202 14"
- 836616 16"
- 836624 24"

8366L

D-RING EXTENDERS \ Extenders

– 18" Web with Choking Loop and D-ring.



– 8366L 18"



## DEVICES

When there is no margin for error on your job site, FallTech Duratech® Self-Retracting Lifelines (SRLs) deliver quick stopping power with minimal impact to the body and anchor point. Rugged, reliable and built to meet the industry's highest standard, Duratech® SRLs bring safety and consistency to even the most challenging work environments.

**DURATECH® \ Cable Self-Retracting Lifeline** #7530

## DEVICES

Sometimes even with the best planning, basic equipment will leave you unprotected and needing a better solution. FallTech's Self-Retracting Devices are built for workplaces where you need greater access to distant anchors, greater mobility and short stopping distances than traditional lanyards can provide.

Durable cast and CNC machined aluminum housing for precision fit and finish

Spring bumper assembly with grip handle to reduce lock-up from free-wheeling


Steel thimble for long life with cable ferrules protected in grip handle

Load-indicating swivel carabiner with 3,600 lbs gate strength



7226


**DURATECH 15 \ Galvanized Cable**  
- 15' SRL with Galvanized Cable;  
Load-indicating Swivel Carabiner.



- 7226	15' Length
- 7227	20' Length

7229


**DURATECH 25 \ Galvanized Cable**  
- 25' SRL with Galvanized Cable;  
Load-indicating Swivel Carabiner.



- 7229	25' Length
- 7232	30' Length

7268


**DURATECH 50 \ Galvanized Cable**  
- 50' SRL with Galvanized Cable;  
Load-indicating Swivel Carabiner.



- 7268	50' Length
- 7265	60' Length
- 726575	75' Length

7226S


**DURATECH 15 \ Stainless Steel Cable**  
- 15' SRL with Stainless Steel Cable;  
Load-indicating Swivel Carabiner.



- 7226S	15' Length
- 7227S	20' Length

7229S


**DURATECH 25 \ Stainless Steel Cable**  
- 25' SRL with Stainless Steel Cable;  
Load-indicating Swivel Carabiner.



- 7229S	25' Length
- 7232S	30' Length

7268S


**DURATECH 50 \ Stainless Steel Cable**  
- 50' SRL with Stainless Steel Cable;  
Load-indicating Swivel Carabiner.



- 7268S	50' Length
- 7266	60' Length

7226SS


**DURATECH 15 \ Steel Cable\Carabiner**  
- 15' SRL with Stainless Steel Cable;  
Stainless Steel Load-Indicating  
Swivel Carabiner.



- 7226SS	15' Length
- 7227SS	20' Length

7232SS


**DURATECH 30 \ Steel Cable\Carabiner**  
- 30' SRL with Stainless Steel Cable;  
Stainless Steel Load-Indicating  
Swivel Carabiner.



- 7232SS	30' Length
----------	------------

7268SS


**DURATECH 50 \ Steel Cable\Carabiner**  
- 50' SRL with Stainless Steel Cable;  
Stainless Steel Load-indicating Swivel  
Carabiner.



- 7268SS	50' Length
- 7266SS	60' Length
- 726675SS	75' Length

7226HW

**DURATECH 15 \ HeavyWeight®**  
- 15' Heavyweight SRL; 400 lbs Capacity,  
Galvanized Cable; Load-indicating  
Swivel Carabiner.



- 7226HW	15' Length
- 7227HW	20' Length

7232HW


**DURATECH 30 \ HeavyWeight®**  
- 30' Heavyweight SRL; 400 lbs Capacity,  
Galvanized Cable; Load-indicating  
Swivel Carabiner.



- 7232HW	30' Length
----------	------------

7268HW

**DURATECH 50 \ HeavyWeight®**  
- 50' Heavyweight SRL; 400 lbs Capacity,  
Galvanized Cable; Load-indicating Swivel  
Carabiner.



- 7268HW	50' Length
- 7265HW	60' Length



7211


**DURATECH 98 \ Galvanized Cable**  
-98' SRL with Galvanized Cable;  
Load-indicating Swivel Carabiner.



- 7211 98' Length
- 7212 138' Length
- 7212145 145' Length
- 7213 195' Length

7211S

**DURATECH 98 \ Stainless Steel Cable**  
-98' SRL with Stainless Steel Cable;  
Load-indicating Swivel Carabiner.



- 7211S 98' Length
- 7212S 138' Length
- 7213S 195' Length



727620

**CONTRACTOR \ Galvanized Cable**  
-20' SRL with Glass-filled Nylon Housing;  
1 Connecting Carabiner and  
1 Load-indicating Swivel Carabiner.



- 727620 20' Length

727630

**CONTRACTOR \ Galvanized Cable**  
-30' SRL with Glass-filled Nylon Housing;  
1 Connecting Carabiner and  
1 Load-indicating Swivel Carabiner.



- 727630 30' Length

727650


**CONTRACTOR \ Galvanized Cable**  
-50' SRL with Glass-filled Nylon Housing;  
1 Connecting Carabiner and  
1 Load-indicating Swivel Carabiner.



- 727650 50' Length

7276WR


**CONTRACTOR \ Dyneema Web**  
-20' Web SRL; Glass-filled Nylon Housing;  
Dyneema Web; Connecting Carabiner;  
Load-indicating Swivel Carabiner.



- 7276WR 20' Length

7270WR

**DURATECH \ Polyester Web**  
-20' Web SRL with Steel Housing;  
Load-indicating Swivel Carabiner.




- 7270WR 20' Length
- 7271WR 15' Length



8262

**FALL LIMITER \ Polyester Web**  
-8' Overhead Retractor; with 1 Steel  
Snap Hook; 1 Swivel and 1 Connecting  
Carabiner.



- 8262 8' Length
- 82624 8' Length  
w/ 8447 Carabiner

7270KV

**WELDTCH \ Kevlar Web**  
-20' Kevlar® Web with Steel Housing;  
Load-Indicating Swivel Carabiner.



- 7270KV 20' Length



5040

RESCUE \ Trauma Relief

- Set of 2 Compatible Hip-packs;  
Exclusive Deployment Design;  
Reflective Webbing Throughout;  
Fits All Full Body Harnesses.



- 5040



Attach hip-packs to left and right sides of harness as shown.



In the event of a fall, simply insert thumbs through red deployment loops.



Pull red loops forward to release pack closure and deploy the full length of the reflective straps.



With thumbs still holding loops, securely connect steel strap-end clips to form a continuous sling.



Now place both feet in the sling and pull up on trailing end of strap to adjust to your height. Step-in sling is infinitely adjustable to relieve sub-pelvic pressure.

5030100

RESCUE \ Controlled Descent

- 100' Controlled Descent Kit,  
4' per second Evacuation;  
with Carabiners and Bag.



- 5030 60'
- 5030100 100'
- 5031 150'
- 5030250 250'



CONFINED SPACE

FallTech confined space systems are designed to provide safe access and emergency rescue for traditional confined spaces. A full range of compatible components allow users the flexibility to plan for a variety of entry and egress scenarios.

Three steel head plates provide added strength and durability

Integral composite pulley within tripod head

Extruded aluminum legs with cast aluminum head and feet provide light weight strength

Slip-resistant foot belting keeps tripod position secure

Cable detent pins secure telescoping leg adjustment



7504

TRIPOD KITS/CONFINED SPACE



7275

TRIPOD

– 6’ to 11’ Adjustable Aluminum Tripod with Integral Pulley and Detent Pins.



– 7275 6’ to 11’

7287

DURATECH / Retrieval

– 82’ 3-Way Retrieval SRL with Galvanized Cable; Mounting Bracket; and Load-indicating Swivel Carabiner.



– 7287 82’ Galvanized Cable  
– 7287S 82’ Stainless Steel Cable

7285

DURATECH / Retrieval

– 60’ 3-Way Retrieval SRL with Galvanized Cable; Mounting Bracket; and Load-indicating Swivel Carabiner.



– 7285 60’ Galvanized Cable  
– 7285S 60’ Stainless Steel Cable  
– 7285SS 60’ Stainless Steel Cable/Carabiner

7290

WINCH

– 60’ Personnel Winch with Galvanized Cable and Swivel Snap Hook.



– 7290 60’ Galvanized Cable  
– 7290S 60’ Stainless Steel Cable  
– 7295 120’ Galvanized Cable  
– 7295S 120’ Stainless Steel Cable

7421

ACCESSORIES

– Aluminum Confined Space Pulley; for Up to 3/8” Cable.



– 7421

7274

TRIPOD

– 6’ to 7’ Adjustable Aluminum Tripod with Bracket and Integral Pulley; Click-lock Adjustment Pins.



– 7274 6’ to 7’ Adjustable

7283

DURATECH / Retrieval

– 60’ 3-Way Retrieval SRL with Galvanized Cable; Mounting Bracket; and Load-indicating Swivel Snap Hook.



– 7283 60’ Galvanized Cable  
– 7283S 60’ Stainless Steel Cable

7282

STORAGE

– 20” Weather-resistant Equipment Bag with Handles; For 3-ways and Winches.



– 7282 20” Length

7280

STORAGE

– 80” Weather-resistant Tripod Storage Bag with Handles; For 7275 or 7274.



– 7280 80” Length

8208

ACCESSORIES

– Retrieval Yoke with 2 Steel Snap Hooks and Connecting Ring; Jacketed Aluminum Spanner Bar; 24”L x 12”W.



– 8208

7296

ACCESSORIES

– Top-Mount Auxiliary Pulley, for Secondary Device on 7274 Tripod.



– 7296



7500

TRIPOD KIT

- Tripod Kit with 7275 Tripod; 7285 3-Way SRL; 7280 and 7282 Storage Bags.



- 7500 Galvanized Cable
- 7500S Stainless Steel Cable

7504

TRIPOD KIT

- Tripod Kit with 7275 Tripod; 7285 3-Way SRL; 7290 Winch; 7421 Pulley; 8450 Carabiner; 7280 and 7282 Storage Bags.



- 7504 Galvanized Cable
- 7504S Stainless Steel Cable

7505

TRIPOD KIT

- Tripod Kit with 7275 Tripod; 7290 Winch; 7280 and 7282 Storage Bags.



- 7505 Galvanized Cable
- 7505S Stainless Steel Cable
- 7510 120' Length



7502

TRIPOD KIT

- Tripod Kit with 7274 Tripod; 7290 Winch; 7280 and 7282 Storage Bags.



- 7502 Galvanized Cable
- 7502S Stainless Steel Cable

7503

TRIPOD KIT

- Tripod Kit with 7274 Tripod; 7283 3-Way SRL; 7290 Winch; 7296 Pulley; 7284 Bracket; 7280 and 7282 Storage Bags.



- 7503 Galvanized Cable
- 7503S Stainless Steel Cable

7501

TRIPOD KIT

- Tripod Kit with 7274 Tripod; 7283 3-Way SRL; 7280 and 7282 Storage Bags.



- 7501 Galvanized Cable
- 7501S Stainless Steel Cable



ITEM #	7275 TRIPOD	7285 3-WAY	7285S 3-WAY	7290 WINCH	7290S WINCH	7280 BAG	7282 BAG
7500	—	—				—	—
7500S	—		—			—	—
7505	—			—		—	—
7505S	—				—	—	—
7504	—	—		—		—	—
7504S	—		—		—	—	—

ITEM #	7274 TRIPOD	7283 3-WAY	7283S 3-WAY	7290 WINCH	7290S WINCH	7280 BAG	7282 BAG	7284 BRACKET	7296 PULLEY
7501	—	—				—	—		
7501S	—		—			—	—		
7502	—			—		—	—		
7502S	—				—	—	—		
7503	—	—		—		—	—	—	—
7503S	—		—		—	—	—	—	—



## KITS

The FallTech Contractor roofer's kit is a turnkey solution built to take the guess work out of fall protection in a residential roofing environment. Ready when you need it, the Contractor roofer's kit is easy to install and combines all the necessary components of a personal fall arrest system in an easy to carry bucket.

**CONTRACTOR \ Roofer's Kit**

#8595A

Multiple user-defined combinations available

Roofer's kits contain harness, shock absorbing lanyard with integral rope grab, vertical lifeline and roof anchor

# KITS


Keep it simple. When you know how you are going to address your fall hazard and your equipment needs are uncomplicated, we have your solution. Roofer's kits, Looped Lanyard and Harness Combinations and Bagged Harness and Lanyard Kits are available to quickly address your problem and get you back to work.







Select the harness and lanyard option best suited for your needs to find the Kit Ordering Number	8259 LANYARD	8259Y LANYARD	82593 LANYARD	8259Y3 LANYARD	8256LT LANYARD
7015 Harness	KIT152595P	KIT1559Y6P	KIT155935P	KIT159Y36P	KIT156LT5P
7016 Harness	KIT162596P	KIT1659Y6P	KIT165936P	KIT169Y36P	KIT166LT6P
7017 Harness	KIT172595P	KIT1759Y6P	KIT175935P	KIT179Y36P	KIT176LT5P
7018 Harness	KIT182596P	KIT1859Y6P	KIT185936P	KIT189Y36P	KIT186LT6P
7007 Harness	KIT072595P	KIT0759Y6P	KIT075935P	KIT079Y36P	KIT076LT5P



Select the harness and lanyard option best suited for your needs to find the Combo Ordering Number	8259L LOOPED LANYARD	82593L LOOPED LANYARD	8259YL LOOPED LANYARD	8259Y3L LOOPED LANYARD	8256LTL LOOPED LANYARD
7015 Harness	CMB158259L	CMB152593L	CMB15259YL	CMB1559Y3L	CMB1556LTL
7016 Harness	CMB168259L	CMB162593L	CMB16259YL	CMB1659Y3L	CMB1656LTL
7017 Harness	CMB178259L	CMB172593L	CMB17259YL	CMB1759Y3L	CMB1756LTL
7018 Harness	CMB188259L	CMB182593L	CMB18259YL	CMB1859Y3L	CMB1856LTL
7007 Harness	CMB078259L	CMB072593L	CMB07259YL	CMB0759Y3L	CMB0756LTL



8595A

FALL PROTECTION \ Roofer's Kit

- 7016 Harness; 8150 Vertical Lifeline, 8368 Shock Absorbing Lanyard with Trailing Grab; 7410 Roof Anchor.



- 8595A  
- 8595RA  
w/ Bag 5007LP

8592A

FALL PROTECTION \ Roofer's Kit

- 7015 Harness; 8149 Vertical Lifeline, 8353LT Shock Absorbing Lanyard with Manual Grab; 7444 Roof Anchor.



- 8592A

9500Z

FALL PROTECTION \ Starter Kit

- 7015 Harness; 8259 Shock Absorbing Lanyard.



- 9500Z

9503Z

FALL PROTECTION \ Starter Kit

- 7015 Harness; 8259Y3 Shock Absorbing Lanyard.



- 9503Z

8593A

FALL PROTECTION \ Roofer's Kit

- 7015 Harness; 8149 Vertical Lifeline, 8353LT Shock Absorbing Lanyard with Manual Grab; 7410 Roof Anchor.



- 8593A

9103JK

FALL PROTECTION \ Roofer's Kit

- 7016 Harness; 8150 Vertical Lifeline, 8368 Shock Absorbing Lanyard with Trailing Grab; 7372 Pass-through Sling Anchor.



- 9103JK

9504Z

FALL PROTECTION \ Starter Kit

- 7007 Harness; 8259 Shock Absorbing Lanyard.



- 9504Z

9505Z

FALL PROTECTION \ Starter Kit

- 7016 Harness; 8259 Shock Absorbing Lanyard.



- 9505Z

9001HS

FALL PROTECTION \ Carry Kit

- 7016 Harness; 8259 Shock Absorbing Lanyard, 5005P Gear Bag.



- 9001HS  
- 9005PS with 7015  
Harness

9003HS

FALL PROTECTION \ Carry Kit

- 7018 Harness; 8259 Shock Absorbing Lanyard, 5005P Gear Bag.



- 9003HS

5005P

STORAGE \ Gear Bag

- Small Gear Bag with Handle; 8" x 11".



- 5005P

5004WP

STORAGE \ Gear Bag

- Water Resistant Gear Bag; with Carry Handles; 17" x 9" x 9".



- 5004WP

9017HS

FALL PROTECTION \ Carry Kit

- 7015 Harness; 8259Y Shock Absorbing Lanyard, 5007LP Gear Bag.



- 9017HS

9010CP

FALL PROTECTION \ Carry Kit

- 7007 Harness; 8259 Shock Absorbing Lanyard, 5005P Gear Bag.



- 9010CP

5007LP

STORAGE \ Gear Bag

- Large Gear Bag with Shoulder Strap and Carry Handles; 10" x 18".



- 5007LP 10" x 18"  
- 5006MP 9" x 15"

5026

STORAGE \ Gear Bag

- Extra Large Duffle Gear Bag, with 2 Shoulder Straps and Carry Handle; 20" x 14".



- 5026



## RIGID OVERHEAD SYSTEMS

Rigid Overhead systems provide all the benefits of rigid track fall protection with a sleek and portable design. With an overall typical weight of 13,800 lbs. these systems can be easily moved with a 15,000 lbs. forklift. Bolt-together components with no welding required. Systems can be designed for multiple workers and utilize either single or dual track design.

### Rigid Overhead Systems

Enclosed track

Bolt together system  
– No welding required

Permanent and  
Portable Systems

# SYSTEMS

Because not all fall hazards are mitigated through traditional personal fall arrest systems, FallTech offers a wide range of solutions to fit the specific needs of your workplace. Whether you are in need of permanent overhead anchorage, roof top fall protection, ladder safety systems or guardrail, FallTech has the solution. We know that each workplace is a little bit different from the next, and we are able to custom engineer and fabricate fall protection solutions to make your workplace safer.



RIGID OVERHEAD SYSTEMS

Blending portability and rigid track fall protection with a single or dual track system for multiple workers, Rigid Overhead systems offers advanced fall protection for a multitude of environments.

CEILING

Uses existing support structure, no floor space required; ideal for situations where straight runs of fall protection coverage are needed, like vehicle applications.

PORTABLE GANTRY

Portable systems easily move around work area with polyurethane or pneumatic tires; easily broken down and moved to new job sites.

FOLD-AWAY

Folds against the wall and out of the way when not in use; fall protection solution for facilities with large overhead cranes.

TRAVELING BRIDGE

Systems provide wide range of movement in multiple directions; provides the most ideal coverage area for larger maintenance applications.



GUARDRAILS

When considering a passive fall protection system, guardrails are a quick and easy-to-install solution. This non-penetrating guardrail system ensures workers are protected with no drilling, and can help you get into OSHA compliance when a passive fall protection system is required.

This guardrail system allows for infinite configurations so you can tailor this system to your exact requirements. Each base can support up to 4 rails, and each rail can be positioned in unlimited directions – giving you the safety and flexibility you need to eliminate the fall hazard.

PERMANENT HORIZONTAL LIFELINE SYSTEMS

Permanent Horizontal Lifeline systems are easily adapted for roof top and overhead use. Capitalizing on the strength and long life of steel cable and advances in the technology of load management, this permanent horizontal lifeline system preserves structural integrity and prevents damage from dynamic loads over long spans.

The in-line damper acts as a shock absorber and reduces peak end-loads by up to 40%. For roof top systems, the unique posts allow for simple installation and rapid repair in the event of a fall. These may be mounted in a variety of different ways to an array of available base plates for use on composition or even standing seam roofs.

For installation on vertical surfaces, we have a variety of engineered brackets, all designed to allow for easy installation and maintenance without overpowering your structure.



XSPlatforms

The XSPlatforms Fall Protection system is maintenance free, patented and certified to the latest standards. The products are made of high-grade aluminum and stainless steel and installation is fast and easy!

XTS-Impact offers a unique, integrated visual fall indicator so the safety status of the anchor points is always clear to users. Installing the XTS-Impact anchor point will take just a few minutes. The system can simply be mounted on top of the existing roofing. XTS-Impact anchor points can be combined with XTS-Linked safety lines allowing optimal freedom of movement while working at heights.







[www.falltech.com](http://www.falltech.com)

©2013 FallTech  
1306 S. Alameda St.  
Compton, CA  
90221-4803

**800.719.4619**  
**323.752.5613**

Tools shown not included.

Product descriptions and specifications  
herein may change without notice.

U.S. and Int'l Patents Pending.

**PART #MC13.2 ALX**